



## VS-88A

8x8 Balanced Stereo Audio Matrix Switcher

---



The **VS-88A** is a high-performance matrix switcher for balanced stereo audio signals. It can route any or all inputs to any or all outputs simultaneously.

### FEATURES

---

- S/N Ratio - 84dB unweighted (1Vpp).
- Control - Front panel, RS-232 (K-Router™ Windows®-based Kramer software is included), RS-485.
- Take Button - Executes multiple switches all at once.
- Memory Locations - Stores multiple switches as presets to be recalled and executed when needed.
- Worldwide Power Supply - 100-240V AC.



## VS-88A

### TECHNICAL SPECIFICATIONS

|                         |   |
|-------------------------|---|
| INPUTS:                 | 8 balanced stereo audio, +4dBu/33k $\Omega$ on detachable terminal blocks.            |
| OUTPUTS:                | 8 balanced stereo audio, +4dBu/50 $\Omega$ (20Vpp max) on detachable terminal blocks. |
| AUDIO BANDWIDTH (-3dB): | 100kHz.   |
| AUDIO S/N:              | 84dB unweighted (1Vpp).   |
| CONTROL:                | 22 front panel buttons, RS-232 and RS-485 control interface.                          |
| AUDIO THD:              | 0.025% (1Vpp, 1kHz).  |
| 2nd HARMONIC:           | 0.013%.   |
| MAX. AUDIO:             | >20dBu.   |
| INDICATORS:             | 8-character display on the front panel.   |
| POWER CONSUMPTION:      | 115/230V AC, 50/60Hz, 16VA max.   |
| DIMENSIONS:             | 19" x 7" x 1U W, D, H, rack mountable.  |
| WEIGHT:                 | 3.5kg (7.8lbs) approx.  |
| INCLUDED ACCESSORIES:   | Power cord.   |

