



VS-88DVI

8x8 DVI Matrix Switcher



The **VS-88DVI** is a high-performance matrix switcher for DVI signals. The unit reclocks and equalizes the signal and can route any or all inputs to any or all outputs simultaneously.

FEATURES

- Max. Data Rate - 6.75Gbps (2.25Gbps per graphic channel).
- HDTV Compatible.
- Kramer Equalization & re-Klocking™ Technology - Rebuilds the digital signal integrity to travel longer distances.
- I-EDIDPro™ Kramer Intelligent EDID Processing™ - Intelligent EDID handling & processing algorithm ensures Plug and Play operation for DVI systems.
- Flexible Control Options - Front panel, IR remote, RS-232 (K-Router™ Windows®-based software is included), Ethernet (Windows®-based Ethernet Configuration Manager & Virtual Serial Port Manager is included).
- Output Disconnect - Each output.
- Front Panel Lockout.
- Memory Locations - Stores multiple switches as presets to be recalled and executed when needed.
- Worldwide Power Supply - 100-240V AC.
- Standard 19" Rack Mount Size - 2U. Rack "ears" included.



VS-88DVI

TECHNICAL SPECIFICATIONS

INPUTS:	8 DVI, 1.2Vpp on DVI Molex 24-pin female connectors; DDC signal 5Vpp (TTL).
OUTPUTS:	8 DVI, 1.2Vpp on DVI Molex 24-pin female connectors; DDC signal 5Vpp (TTL).
MAX. DATA RATE:	6.75Gbps (2.25Gbps per graphic channel).
COMPLIANCE WITH STANDARDS:	Supports DVI 1.1.
MAX RESOLUTION:	Up to UXGA; 1080p, 1920x1200.
POWER CONSUMPTION:	100–240V AC; 50/60Hz, 43VA.
CONTROLS:	Front panel buttons, infrared remote control transmitter, RS-232, Ethernet.
DIMENSIONS:	19" x 7" x 2U W, D, H.
WEIGHT:	2.5kg (5.5lbs) approx.
INCLUDED ACCESSORIES:	Power cord, infrared remote controller, null-modem adapter, rack "ears".

