

ULD SERIES

When it comes to a dimmer pack you can trust, the ULD ranks as the industry leader in small portable dimming. Production and rental companies alike have come to rely on the ULD for a wide variety of uses. The solid design and construction assure that they will handle the most demanding conditions no matter what the environment. Schools and houses of worship will also appreciate the simple setup and rock solid performance.

Features:

- 25 Amp SSR power devices
- Display based menu system
- Selectable curves
- Over-temp/Over-volt protection
- Professional quality noise filtering
- Optional Wireless DMX by Wireless Solutions



Leprecon LLC

Hamburg, MI 48139, USA

PH 888-422-3537, FAX 810-231-1631

lepls@leprecon.com

www.leprecon.com



Designed and Built in USA

THE ULD SERIES FROM LEPRECON

Each ULD dimmer is equipped with dual 25 Amp SCR's, illuminated magnetic breakers, and over-volt and over-temp protection. Fully encapsulated chokes come standard with every dimmer to further ensure quiet operation. Through the display based menu system, each channel can be defined as a linear, non-dim, fluorescent or fixed intensity level. These are just some features that set the ULD apart from other dimmer packs on the market.

Features on all ULD dimmers:

- Illuminated magnetic breakers
- Over-temp/Over-volt pack protection
- 4 programmable output settings per channel:
Linear, non-dim, fluorescent, or fixed intensity
- 25 Amp SSR per channel
- Encapsulated chokes for quiet operation
- LED Display
- DMX-512-5 pin M/F XLR
- Built-in mounting bracket
- Optional bracket available for horizontal mounting
- Rated continuous use duty cycle on all 15 Amp models

ULD 360 Tree-Mount Dimmers

	ULD-360 Stage Pin	ULD-360-HP Stage Pin	ULD-360 Duplex	ULD-360-HP Duplex	*ULD-360-HP Stage Pin-20A	*ULD-360-HP Duplex-20A
Part Number	90-06-0256	90-06-0251	90-06-0254	90-06-0253	90-06-0271	90-06-0270
Channels	6	6	6	6	6	6
Output Connector	Stage Pin	Stage Pin	Duplex	Duplex	Stage Pin	Duplex
Power In Plug(s)	Nema 5-15	2 Nema 5-15	Nema 5-15	2 Nema 5-15	2 Nema 5-20	2 Nema 5-20
Magnetic Breakers	15 Amp	2-15 Amp	15 Amp	2-15 Amp	2-20 Amp	2-20 Amp
Max Watts per pack@120V	1800	3600	1800	3600	3600	3600
Package weight-lbs.	10	12	10	12	13	12

*Non-ETL listed packs.

Also available in HP - 19 pin female output, ETL listed. Call factory for pricing and availability

ULD 340 Tree-Mount Dimmers

	ULD-340 Stage Pin	ULD-340-HP Stage Pin	ULD-340 Duplex	ULD-340-HP Duplex	ULD-340 Twistlock	ULD-340-HP Twistlock
Part Number	90-06-0258	90-06-0257	90-06-0259	90-06-0260	90-06-0255	90-06-0252
Channels	4	4	4	4	4	4
Output Connector	Stage Pin	Stage Pin	Duplex	Duplex	Twistlock	Twistlock
Power In Plug(s)	Nema 5-15	2 Nema 5-15	Nema 5-15	2 Nema 5-15	Nema 5-15	2 Nema 5-15
Magnetic Breakers	15 Amp	2-15 Amp	15 Amp	2-15 Amp	15 Amp	2-15 Amp
Max Watts per pack@120V	1800	3600	1800	3600	1800	3600
Packaged weight-lbs.	10	12	10	12	11	13

Length, Width, Depth- Inches for all ULD dimmers - 15.90 x 5.85 x 4.10



Wireless DMX Models

Wireless DMX is an optional add-on package to the ULD series dimmers. With the wireless receiver built-in to the ULD dimmer, users can conveniently and reliably control up to 512 channels of DMX. Comes standard with 2 dBi antenna and LED indicator for power and DMX presence. Paired with a wireless DMX transmitter the wireless system has a range of up to 2300 ft in line of sight from console.

ULD-340-SP, Duplex, 4 Ch, ETL listed
 ULD-340-HP, Duplex, 4 Ch, ETL listed
 ULD-360-HP, Stage Pin, 6 Ch, ETL listed
 ULD-360-HP, Duplex, 6 Ch, ETL listed
 ULD-360, 20A-HP, Duplex, 6 ch



FULL TWO YEAR WARRANTY

For a period of two years from the date of sale, Leprecon, LLC, will replace any defective parts and will repair any defective module returned to the factory prepaid, without charge for parts or labor. Please consult your dealer for full warranty details.

Leprecon®
 Lighting for Professionals

www.leprecon.com

Copyright Leprecon LLC 28-0065E