

Full HD (USB3.0/HDMI) PTZ Camera



FEATURES

- 2 Megapixel 1/2.8-inch Sensor
- Full-HD Video: 1920x1080p, 1280x720p
- High Speed: 60, 50, 30, 25 fps
- 10x Optical Zoom 6.53~62.18mm (F1.8~2.8) - 12x Digital Zoom
- USB3.0 plus HDMI & Composite (CVBS) simultaneous outputs
- Pan-Tilt Range: 350 degree Horizontal Pan-120 degree Vertical Tilt (widest on the market)
- Built-in Mic and external audio input
- Control via PC-UI Gui interface, IR Remote, RS232, RS422/485 (Visca)
- Integrate into a variety of familiar UC video programs and apps
- Extreme Quiet PTZ movements with 128 presets
- Shelf & ceiling mountable with 1/4"-20 including flippable image ability

Mounting Options

CV610-U3-CM
Ceiling Mount



CV610-U3-WM
Wall Mount



Marshall Electronics Teleconference PTZ Camera is designed to deliver broadcast quality video to Teleconference and Pro A/V applications of all types. USB3.0 support provides ability to use state of the art video performance as high as 1920x1080p60/50fps. Small size makes CV610-U3 versatile and able to be integrated into teleconference & huddle room environments using familiar UC video applications.

Rear I/O functions

1. 12V DC Power Port

Connect the supplied AC power adaptor and cord.

2. Extension Module Port

Extension Port includes options such as RS232/422/485 control, CVBS output, HDMI output, & external Audio input

3. USB 3.0 Port

USB3.0 cable comes with each camera and carries the video signal, audio, and PTZ control (optional)



Breakout Cable (included)

1. Camera Port (connect to rear of camera)
2. Composite (CVBS) video output
3. RS232 Control Port: RX(1), TX(2), GND(3), NC(4)
4. Audio line IN (3.5mm jack)
5. HDMI video output
6. RS422/485 Control Port: GND(1), T+(2), T-(3), R+(4), R-(5)

