

## M-LYNX-702 | 7" Rackmountable 1024 x 600 LCD Display



- High resolution 1024 x 600, bright, colorful display with no-compromise input selections for each screen
- Digital inputs: HDMI, 3GSDI with loop-through (auto selects HDSDI/SDI)
- Analog inputs: Component and Composite with loop-through
- Special features: Selectable markers, 1:1 pixel mapping, Over scan and H/V delay modes, P-P, View individual colors
- Audio de-embedding and monitoring via front panel headphone jacks
- Built-in LED tally indicators (Red, Green, Yellow)
- Slim design and 3RU size
- Power using included 12-volt supply or use standard 4-pin XLR
- Selectable English and Spanish on-screen displays

The **M-LYNX-702** Dual 7" LCD display is a feature-packed, economical solution perfect for fly-packs, control rooms, routing rooms and countless other video system applications. Multiple video inputs set this product apart from similar-looking products. With the M-LYNX-702, you are not limited to the single SDI connector you may find on competitor models. With a full complement of digital and analog connections for each screen, when the unexpected happens, you will be ready. Standard power and tally connections as well as a logical menu structure make this display an easy choice for flexible system designs.

*Features, specifications, pricing, and dimensions are subject to change without notice.*

*Physical appearance of products may vary slightly from images shown on this document. Please visit our website for updates and information.*

## M-LYNX-702 Specifications

<b>Number of Panels</b>	2
<b>Panel Size</b>	7" rack mount, 3RU High
<b>Resolution (Pixels)</b>	1024 x 600
<b>Aspect Ratio</b>	16:9
<b>Active Area</b>	153.6 (W) mm x 90.0 (H) mm
<b>Backlight</b>	LED
<b>Viewing Angle</b>	150°
<b>Brightness (in cd/m<sup>2</sup>)</b>	250
<b>Contrast Ratio</b>	700:1
<b>Digital Video Inputs</b>	3GSDI x 1 (conforms to SMPTE-292M, 259M, 424M) with loop-out HDMI x 1
<b>Analog Video Inputs</b>	Component Y,Pb,Pr x 1 (loop-out) Composite x 1 (loop-out)
<b>Audio Inputs</b>	Accepts HDMI and SDI embedded audio plus analog L,R via RCA
<b>Audio Outputs</b>	Front panel 3.5mm stereo headphone jack
<b>Control Inputs</b>	Tally 9-pin D-Sub port for GPI input Mini USB Service Port
<b>Power</b>	7 to 16-volts DC, 12-volts typical via 5.5mm jack or 4-pin XLR
<b>Compliance</b>	FCC-Class A, CE, RoHS
<b>Dimensions</b>	19"W x 5.2"H x 1,7"D
<b>Weight</b>	5 lbs
<b>Mounting Points</b>	4 x 1/4"-20
Warranty One year standard, two years with product registration	