


## America's Leading Innovator of Cost Effective Prompter Designs

www.teleprompters.com



Specifications	SP-160HB
Viewable Size	15 inch
Brightness	1800 NTS
Signal Input	SVGA, NTSC S-Video
Video Input Impedance	1 VOLTS P-TO-P
Input Voltage	100-240 VAC 12 Volt DC
Resolution	1280x1024
Power Consumption	70 Watts
Input Connector	15-pin D-Type BNC, 4-Pin
Special Features	Scan-Reverse BNC Loop



## **Introducing the new OUTDOOR** Speechprompter...SP-160HB

\*Dual 15" LCD Day-Bright monitors with multiple inputs and Metal LCD cabinet

\*Includes distribution-amp

\*12.75"x10" Beamsplitter Mirrors 12.75"x10" Tinted Mirrors 12.75"x10" True Mirrors

\*Mirrors are vertically adjustable and can be tilted for any individual needs

\*Monitors are placed on the floor and are protected by metal housing

> \*Housings "nest together" for easy portability

\*All metal components with a durable powder coat finish. Extremely tough!

\*3 year conditional warranty. It doesn't get better than that!

\*Generally in stock & ready to ship.

\*250 Dealers worldwide are ready to serve you!

Contact us today with any questions you may have.

Phone 920-232-0220 Fax 920-232-1225 sales@teleprompters.com

www.teleprompters.com





