


## America's Leading Innovator of Cost Effective Prompter Designs

www.teleprompters.com



Specifications	SP-220HB
Viewable Size	19 inch
Brightness	1650 NTS
Signal Input	SVGA, NTSC S-Video, DVI
Video Input Impedance	1 VOLTS P-TO-P
Input Voltage	100-240 VAC 12 Volt DC
Resolution	1280x1024
Power Consumption	90 Watts
Input Connector	15-pin D-Type BNC, 4-Pin
Special Features	Scan-Reverse BNC Loop



## Introducing the new OUTDOOR Speechprompter...SP-220HB

\*Dual 19" LCD Day-Bright monitors
with multiple inputs and
Metal LCD cabinet

\*Includes distribution-amp

\*15.5"x12.75" Beamsplitter Mirrors 15.5"x12.75" Tinted Mirrors 15.5"x12.75" True Mirrors

\*Mirrors are vertically adjustable and can be tilted for any individual needs

\*Monitors are placed on the floor and are protected by metal housing

\*Housings "nest together" for easy portability

\*All metal components with a durable powder coat finish.

Extremely tough!

\*3 year conditional warranty. It doesn't get better than that!

\*Generally in stock & ready to ship.

\*250 Dealers worldwide are ready to serve you!

Contact us today with any questions you may have.

Phone 920-232-0220 Fax 920-232-1225 sales@teleprompters.com

www.teleprompters.com







