



AW2000 • All Weather Enclosure



The AW2000 solves the outdoor problem with a cost effective alternative. It can be used for connectors, controls, switches and devices where weather is the worst enemy. Neutral warm gray color compliments most exterior surfaces. Features full length hinge for strength and rigidity.

Dimensional Data:

Overall enclosure w/ mounting tabs 10"Lx6.5"Wx3.754"D Exterior enclosure base: 8"Lx5"Wx2.4D w/ 12" & 3/4" combo knock outs Interior enclosure base: 7.5"Lx4.5"Wx2"D Door exterior: 8.7"Lx5.5"Wx1.4"D

Door interior: 7.5"Lx4.8"Wx1"D to ModuLine Insert Panels

ModuLine Insert Panels MPK - XLR Type MPP - Decora MP8 - Blank MPQ - Data





MPU - MAAP



MPC - Custom

*For greater flexibility, MPK, MPM and MPU accept all Mystery Electronics FlexiConn series ctors. Consult website for additional panel offering

MPJ - AAP

- UL Listed high impact, UV protected composite exterior meets NEMA 3R. UL3R and IEC IP32 ratings
- Accepts 2ea ModuLine Insert Panels (up to 8ea XLR type connectors, or active devices)
- Padlockable and fully weather proof when not in use
- Rugged interior chassis of 11 gauge steel
- Applications include:

Sports fields - intercom and portable speaker connections, remote truck interface, stadiums

Schools - bus call station, A/V connections

Hotels - banquet facilities, meeting rooms, poolside controls

Houses of worship - fellowship halls

Commercial / Industrial - exterior controls and connectors

Institutional - intercom stations, constrols, audio, video, tel & data

Specialty - parks, band shells, cruise ships



6438 Morton Road Greenbrier, TN 37073 800 798 2256 sales 615 643 8460 voice 615 643 8464 fax sales@mysteryelectronics.com EB-A27-00

floor box solutions since 1979