

Osprey® AHCA-2

Analog to HDMI Converter

Professional Composite / S-Video / Component to HDMI Converter

This Non-Scaling Analog to HDMI Video Converter accepts any NTSC / PAL Composite, S-Video or Component Video Signal as well as unbalanced or balanced stereo audio and converts it to HDMI Video with embedded Audio.





Technology

10-bit analog to digital conversion of CompositeS-Video and Component Video

Video Inputs

Composite/CVBS/S-Video: 480i, 576i (PAL/NTSC) Component: 480i, 480p, 576i, 576p, 720p, 1080i

Audio Inputs

Unbalanced Stereo Audio (¼" to 2x RCA) Balanced Stereo Audio (2 x ¼" to XLR)

Output

HDMI with embedded Audio (RGB 4:4:4)

DIP-Switches

Video Format Selection Audio Format Selection

Dimensions (including BNC's)

3.7" L x 3.7" W x 0.9" H (94mm L x 94mm W x 23mm H)

Power Connector

Locking Mini B USB

Power

+5 VDC @ ~2.5W

Warranty

1 year limited hardware warranty

In the Box

Converter
Audio Cable ¼" to 2x RCA
3x BNC to RCA Adapters
Locking USB Power Cable
USB Power Supply
Mounting Brackets

20160803

© 2016 Osprey Video. Osprey® & SimulStream® are registered trademarks of Osprey AG. All other trademarks are the property of their respective owners. Product specifications and availability may