# SUA747PU



Display size 32"- 50"



Max load 60lb (27kg)



### **Additional Features**

- Arm retracts to 1.85" (47mm) and extends up to 24.85" (631mm) from wall
- One-Touch™ tilt mechanism allows adjustment of +15/-5° without the use of tools
- Up to ±90° of side-to-side swivel
- Added ±5° of roll for postinstallation display leveling without the use of tools
- Up to ±0.5" (13mm) of vertical adjustment for post-installation leveling and height adjustment fine-tuning
- Internal cable management provides clean, professional installation finish
- Universal mount fits displays with mounting patterns 200 x 100 to 400 x 400mm
- Landscape or portrait mounting options increases display versatility
- The I-Shaped Adaptor plate's innovative design helps avoid blocking connections on back of display
- \* Designed for use with displays that are less than 3" (76mm) deep





# DesignerSeries™ Universal Ultra Slim Articulating Wall Mount

FOR 32" TO 50" ULTRA-THIN DISPLAYS\*

One of the thinnest wall arm mounts on the market, the Peerless-AV® DesignerSeries™ Universal Ultra Slim Articulating Wall Mount is designed exclusively for ultra-thin displays. The SUA747PU is built to hold displays firmly in any position - landscape or portrait while still offering an ultra-low profile. An innovative I-shaped adaptor plate makes it easy to access the back of the display, keeping hardware hidden, and features internal cable management, providing a clean, professional look that transitions smoothly from the wall to the display. With a gloss black finish, the SUA747PU matches any décor.

> Full-motion capabilities allow you to swivel, tilt, extend or retract your display for the perfect viewing angle.





Swivel, tilt, extend or retract the display for the perfect viewing angle



Integrated cable management keeps cords and cables out of the way



Comes in color packaging with included installation hardware and easy to follow instructions.

Please visit peerless-av.com/en-us/patents for patent information.

SUA747PU

DesignerSeries™ Universal Ultra Slim Articulating Wall Mount for 32" to 50" Ultra-Thin Displays\*

\* Designed for use with displays that are less than 3" (76mm) deep

# **Product Specifications**

	DIMENSIONS (W x H x D)	PRODUCT WEIGHT	LOAD CAPACITY	FINISH	AVAILABLE COLORS
SUA747PU	20.25" x 16.94" x 1.85"-24.85" (514 x 430 x 47-631mm)	12.37lb (5.61kg)	60lb (27kg)	Scratch resistant fused epoxy	Gloss black

# **Package Specifications**

	PACKAGE SIZE (W x H x D)	PACKAGE SHIP WEIGHT	PACKAGE UPC CODE	PACKAGE CONTENTS	UNITS IN PACKAGE
SUA747PU	21.25" x 3.25" x 19.50" (540 x 86 x 495mm)	16.75lb (7.60kg)	735029306382	Wall mount, wall and display installation hardware, installation instructions	1

## **Accessories**

ACC919: Security Fasteners

IBA2(AC)(-W), IBA3(AC)(-W): Recessed Cable Management and Power Storage Accessory Box


**IBA4-W:** Easy Mount Recessed Low Voltage Cable Plate

IBA5-W: Recessed Low Voltage Media Plate with Duplex Surge Suppressor

ESHV models: AV Wall Shelves
WSP756: Metal Stud Wall Plate


All dimensions = inch (mm)





1,85"
(47mm)

SIDE VIEW COLLAPSED



24.85"
(631mm)

SIDE VIEW EXTENDED

+15°/-5° TILT

# **Architect Specifications**

The DesignerSeries™ Universal Ultra Slim Articulating Wall Mount shall be a Peerless-AV model SUA747PU and shall be located where indicated on the plans. Assembly and installation shall be done according to instructions provided by the manufacturer.

Visit peerless-av.com to see the complete line of AV solutions from Peerless-AV, including outdoor displays, wireless, kiosks, digital audio, display mounts, projector mounts, carts/stands, and a full assortment of accessories.

### Peerless-AV

2300 White Oak Circle Aurora, IL 60502 USA

(800) 865-2112 (630) 375-5100 Fax: (800) 359-6500

### Peerless-AV Europe

Unit 3 Watford Interchange Colonial Way, Watford Herts, WD24 4WP United Kingdom

+44 (0) 1923 200100 Fax: +44 (0) 1923 200101

### Peerless-AV de México

Ave de las Industrias 413
Parque Industrial Escobedo
Escobedo, N.L.,
Mexico 66050

+52 (81) 8384-8300 Fax: +52 (81) 8384-8360

