



RM68 Zone Wolf

The RM68 is a three microphone, six stereo RCA source mixer that combines the signals and routes them to either of two zones or both. Microphone and Source inputs 1 through 3 share Volume sliders 1 through 3. Microphone One features a talkover function, activated automatically when signal is present at Mic One and the Talkover switch is engaged. +12 VDC phantom power is available for each individual microphone input. Bass, Treble and overall Volume controls are provided for each zone output. Applications for the Zone Wolf include restaurants, hotels, schools, churches or factories.

FEATURES:

- Two separate zones with six assignable inputs
- Three XLR balanced Mic inputs with phantom power
- Six stereo RCA inputs
- Bass and Treble controls for each zone
- Automatic talkover on Mic One to the assigned zone
- Master level for each zone
- RCA and 1/4" stereo outputs
- Rugged design and steel chassis for demanding road use, or installation

SPECIFICATIONS

600 Ω XLR balanced Input Impedance: Mic:

22K Ω RCA unbalanced Source:

Bus Input: $22K \Omega$ unbalanced Max Input Level: -14 dBV balanced Mic:

> Source: $+24 \, \mathrm{dBV}$

3: XLR, 6: stereo RCA, 2: 1/4" (Bus inputs) Input Connectors:

Outputs: 1/4" balanced Main out, 1/4" unbalanced Prefade out

Max Gain: 60 dB Mic: Line: 26 dB

12 dB boost/cut

Tone Control: +12 VDC Phantom Power: Output Level: $+17 \, \mathrm{dBV} \, \mathrm{max}$

Output Impedance: 51Ω

Phase Shift: <10 degrees, 20Hz to 20 kHz

Max S/N ratio: 106 dB THD: <.003%

CMRR: >52 dB (Mic) Size: 19" x 1.75" x 6"

(48.3 x 4.5 x 15 cm)

Weight: 5 lbs. (2.3 kg)

info@rolls.com • www.rolls.com