

16-Port Cross-platform DVI-D Switch

with USB 2.0 and Stereo Audio

Control 16 Computers, PC or Mac on one Display Up To 20 Feet Away with Stereo Audio and USB 2.0

The DVN-16P is a cross-platform switch capable of sharing a DVI-D monitor, stereo speakers and USB 2.0 devices between sixteen computers. It is RS-232 and Infrared compliant, capable of being controlled remotely via software.

- Supports Mac, PC, Linux and Sun DVI
- Supports High Resolution1920x1200 60Hz WUXGA
- Uses universal DVI Single Link connectors
- Zero pixel loss with TMDS signal correction
- Supports all USB 2.0 Devices (Flash Drives, Printers, Cameras, Scanners, etc.)
- Supports USB 2.0 keyboard and mouse
- Balanced stereo audio output
- Front panel tactile switch with LCD display for local control
- Full IR and RS-232 control for remote control
- Optional TCP/IP control





SIMPLE APPLICATION

DVI-D Maxtrix Switching made Easy

SmartAVI's DVN-16P matrix switch provides an easy and dynamic approach to switching up to 16 high-definiton DVI-D video, stereo audio and USB 2.0 sources. The switching functions can be controlled either directly via the front panel, or remotely using RS-232, IR, USB or TCP/IP. The switch comes with our Windows®-based software for RS-232 control, SmartControl, which is easy to understand and simple to use – a cornerstone of all SmartAVI products.

The switch features fully transparent USB 2.0 switching that allows for USB 2.0 devices to be connected at the console. Flash memory drives, USB cameras, and other USB peripherals can be switched between up to 16 computers.

Another feature of the DVN-16P is EDID learning, which allows the switch to emulate the DDC signal of the attached monitor to all the attached devices, not just the selected port. It learns the EDID information of the monitor and emulates it to the attached devices, even when their ports are not selected. This is very important because if the EDID information is not emulated when a computer is booting up, the computer will default to a low-resolution setting.

Application Diagram



The DVN-16P has a broad range of applications, but its main function is to centralize the access to several computers into one console. Not only does it function like a KVM, it has USB support. This allows a user at the console to use USB devices that would otherwise be unavailable with conventional KVMs. For example, it allows a user to use a flash memory drive or camera without having to plug it directly into the remote computer. In the medical or industrial field for example, where it may not be practical (or safe) to have one or more CPUs in the general vicinity, the DVN-16P is a perfect solution.

Applications

- Server Collocation
- Digital Signage
- Airports
- Dealer Rooms
- Control Rooms
- Audio/Visual Presentations
- Shopping Centers
- Hotels/Resorts
- KVM Switches

FLEXIBLE CONTROL



RS-232: Controlling the DVN-16P has never been simpler with SmartControl software. With SmartControl you can assign a unique name to each port on the Switch, allowing full customization of projects to meet your needs. Although all the functions of the matrix are available locally on the front panel of the DVN-16P, using SmartControl allows for simplified customization of all the matrix functions.



USB: Computers that do not have an RS-232 port can connect to the DVN-16P via SmartAVI's USB to RS-232 converter. Utilize all the control of an RS-232 control interface with the simple and common USB interface. This solution is perfect for laptops and newer computers that only have a USB port.



IR: Many system proffesionals prefer the IR control interface because it offers greater flexibility to manage the DVN-16P at a distance. In some cases, the switch may be located some distance from the console and it is necessary to control the matrix with Infrared control.




TCP/IP: Remote control is essential to real-time management of the DVN-16P. SmartAVI's SMTCP module is the perfect solution to effective remote management. Simply connect the SMTCP module to the DVN-16P and connect from anywhere on the internet. When you need to make a change, but can't be there in person, the SMTCP makes remote control a snap.



EDID UTILITY: With SmartAVI's EDID Utility it is possible to upload multiple EDID to the Matrix. EDID is information sent by a display back to the computer, indicating the maximum resolution that display is capable of rendering. When controlling multiple displays it is critical to be able to manage the EDID information. With our EDID utility, managing your displays is simple.

SPECIFICATIONS



DVN-16P Front



DVN-16P Rear

| VIDEO | |
|---------------------|---------------------------------------|
| Format | DVI-D Single Link |
| Maximum Pixel Clock | 165 MHz |
| Input Interface | (16) DVI-D 29-pin female |
| Output Interface | (1) DVI-D 29-pin female |
| Resolution | Up to 1920 x 1200 @60Hz |
| DDC | 5 volts p-p(TTL) |
| Input Equalization | Automatic |
| Input Cable Length | Up to 20 ft. |
| Output Cable Length | Up to 20 ft. |
| AUDIO | |
| Frequency Response | 20 Hz to 20 KHz |
| Impedance | 600 ohm |
| Nominal Level | 0-1.0 V |
| Common Mode | Rejection at 60dB |
| Input Interface | (16) 3.5 mm Stereo Audio |
| Output Interface | (1) 3.5 mm Stereo Audio |
| USB | |
| Signaling | USB 2.0, 1.1 and 1.0 w/ Internal Hub |
| Input Interface | (16) USB Type B |
| Output Interface | (2) USB Type A |
| CONTROL | |
| Front Panel | Tact Switch |
| RS232 | Via Software @ 9600 bps |
| IR | Via Remote Control with IR-EYE Type 3 |

| OTHER | |
|-----------------|----------------------------------|
| Power | External 100-240 VAC/5VDC4A @20W |
| Dimensions | 17"W x 3.5"H x 6.75"D |
| Weight | 10 lbs. |
| Approvals | UL, CE, ROHS Compliant |
| Operating Temp. | 32-131°F (0-55 °C) |
| Storage Temp. | -4-185 °F (-20-85 °C) |
| Humidity | Up to 95% |
| Emulation | NO KEYBOARD OR MOUSE EMULATION |

| ORDERING INFORMATION | | |
|----------------------|---|--|
| Part No. | Description | |
| DVN-16PS | DVNET-16P, 16X1 DVI-D, USB2.0, Audio switch Includes: [DVN-16P & (PS5VD4A)] | |

Many leading companies have recognized and embraced the innovation of SmartAVI's technologies and have successfully incorporated them into their organizations. Users of SmartAVI include:





SmartAVI, Inc. / Twitter: smartavi - 2840 N. Naomi Ave. Burbank, CA 91504 - Tel: (818) 565-0011 Fax: (818) 565-0020 - http://www.SmartAVI.com

