

12" 380W Self-Contained Portable P.A. System With Built-In USB MP3 Player and iPod® Dock

Speco Technologies' PAP160A is a high-powered, portable, self-amplified sound system and is the ideal solution for classrooms, training rooms, auditoriums, houses of worship, traveling presenters and much more. The unit contains a 12" woofer and 1.3" tweeter with a built-in 380W amplifier, iPod® Dock and USB MP3 player.

PAP160A 380 Watts

Features

1. USB Connector SD Connector: Connect Flash drive with MP3 files for play via built-in MP3 player (#12). MP3 / iPod® input can also be turned on/off
2. MP3 / iPod® level: Controls the volume level of the MP3 (#12) or iPod®
3. MIC Input: Connect a dynamic microphone through either 3-pin XLR connector or 1/4" jack
4. MIC level: Control volume of microphone connected via MIC input (#3)
5. Line Input: Connect device with line level output such as CD player, tuner or mixer through either RCA balanced input or 3-pin XLR.
6. Line Input Level: Control volume level of the Line input (#5)
7. Output: Send output signal to another amplifier or to another PAP160A
8. Bass & Treble: Control the low & high level frequency tone levels.
The range is selectable between -12dB to +12dB
9. iPod® Dock: Dock will play output from iPhone® or iTouch®
10. Main Power Supply: Power cable connection
11. Power Switch: Turns unit on/off
12. MP3 Player & Controls: Display information for any MP3 files connected via the USB and SD card input. There are 5 control buttons (from left to right):
 - a. Play/Pause
 - b. Stop
 - c. Play options: Random (default): Play the songs on the drive in a random order once through, Repeat One: Repeat the current song & Repeat All: Continue to randomly play all songs.
 - d. Reverse: One quick press & release will go to the previous song Holding the button down will rewind through the current song
 - e. Forward: One quick press & release will go to the next song Holding the button down will forward through the current song
13. Power LED: Lights when device is ON.
14. Clipping LED: Lights when applied input signal reaches distortion.
Reduce input level in order to eliminate distortion.



(rear of unit - iPod® not included)

Specifications

MP3 Player	USB with LCD display	Woofer	12" polypropylene,
iPod® Dock.....	Yes		65mm voice coil,
Frequency Response	40Hz – 17kHz		50 oz. magnet
Sensitivity	96±2dB (1W/1M)	Tweeter.....	1.3" titanium
RMS Power	160W	Voltage.....	110VAC 50 – 60Hz
Max. Power.....	380W	Dimensions.....	17.5" (W) x 25.2" (H) x 14" (D)
		Weight	35 lbs.

iPhone, iPod, and iPod touch are trademarks of Apple Inc., registered in the U.S. and other countries.

Speco Technologies is constantly developing and improving products.

We reserve the right to modify product design and specifications without notice and without incurring any obligation.

Rev. 6/20/12

For more information contact Speco Technologies

200 New Highway, Amityville, NY 11701 • Toll Free: 1-800-645-5516 • Fax: 631-957-9142 or 631-957-3880
www.specotech.com