

Spec Sheet

HDMI® to VGA Video Adapter Converter with Audio for Desktop PC / Laptop / Ultrabook - 1920x1200

StarTech ID: HD2VGAA2



The HD2VGAA2 HDMI® to VGA Adapter Cable enables you to connect an HDMI output device, such as a laptop video output or digital media extender to a VGA display device (monitor, projector) by converting the HDMI video signal from the output device into a VGA output and separate 2-channel analog audio. The HDMI to VGA adapter is intended for displaying user generated content such as presentations, documents, and work sheets onto a VGA projector or monitor. The adapter can also extend your computer's desktop to double your workspace and increase productivity.

The versatile converter supports resolutions including high definition 1080p, up to 1920x1200, which eliminates the expense of upgrading a VGA display for the sake of compatibility, and doesn't require a separate power adapter which saves installation time and hassle.

Backed by 2-year warranty and free lifetime technical support.

Applications

• Connect your HDMI-enabled laptop or ultrabook to a VGA projector or display in boardrooms, hotel rooms, in the office, or at home



Spec Sheet

Features

- Supports PC resolutions up to 1920x1200 (WUXGA) and HDTV resolutions up to 1080p
- 2-channel analog audio output
- Easy to use with no software required
- Compact, lightweight design

Technical Specifications

| Warranty | 2 Years |
|--------------------------------------|--|
| Audio | Yes |
| Converter Type | Format Converter |
| Audio Specifications | 2 Channel |
| Maximum Analog Resolutions 1920x1200 | |
| Wide Screen Supported | Yes |
| Connector A | 1 - HDMI (19 pin) Male Input |
| Connector A | 1 - USB Micro-B (5 pin) Female |
| Connector B | 1 - VGA (15 pin; High Density D-Sub) Female Output |
| Connector B | 1 - 3.5 mm Mini-Jack (3 Position) Female Output |
| Color | Black |
| Enclosure Type | Plastic |
| Product Height | 0.6 in [15 mm] |
| Product Length | 9.8 in [250 mm] |
| Product Weight | 1.6 oz [44 g] |
| Product Width | 1.8 in [45 mm] |
| Humidity | 40%-85%RH |
| Operating Temperature | 0°C to 60°C (32°F to 140°F) |
| Storage Temperature | -10°C to 70°C (14°F to 158°F) |
| Shipping (Package) Weight | 2.3 oz [66 g] |
| Included in Package | 1 - HDMI® to VGA Adapter Converter |



Hard-to-find made easy®

Certifications, Reports and Compatibility

C€







Spec Sheet

www.startech.com/m 1 800 265 1844