

1U 15" Rackmount LCD Console - USB + PS/2

Product ID: RACKCONS1501



The RACKCONS1501 1U LCD Rack Console provides a complete keyboard, video and mouse control point, integrated neatly into only 1U of rack space, providing total KVM control right from your server rack.

The KVM rack console integrates a 15in TFT-LCD monitor, full 105-key keyboard and touchpad together into a durable rack-mountable console. When the console is not in use, it's as simple as folding the display down like a laptop computer and sliding it into your server rack or cabinet on sturdy mounting rails (included). To prevent unauthorized access to your connected systems, the console offers a key lock to secure the lid closed.

Offering consolidated control from a centralized location, the KVM console can be connected to virtually any multi-port KVM switch, for scalable connection to multiple servers/computers. Plus, the console supports connections to both PS/2 and USB controlled computers, accommodating both legacy and newer servers or KVM switches.

Backed by a Startech.com 2-year warranty, and free lifetime technical support.

Certifications, Reports and Compatibility



Applications

- Centralized control of a single system, or dozens of PCs when connected to a KVM switch
- Improving the internal space-efficiency of existing cabinets
- Manage cabinet-mounted servers and KVM switches

Features

- Supports resolutions up to 1280x1024
- Key-lock to avoid unauthorized access
- VGA video input support
- Durable 1U rack-mountable design
- Compatible with USB or PS/2 PCs and KVMs
- 15" Active matrix TFT LCD display
- OSD (On Screen Display) controls for LCD display

Hardware	Warranty	2 Years
	Audio	No
	Daisy-Chain	Yes
	Display Size	15in
	Key Lock	Yes
	KVM Ports	1
	Number of Monitors Supported	1
	Panel Type	Active Matrix TFT LCD
	PC Interface	USB and PS/2
	PC Video Type	VGA
Rack-Mountable	Yes	
Performance	Aspect Ratio	Standard (4:3)
	Brightness	250 cd/m ²
	Contrast Ratio	400:1
	IP Control	No
	Maximum Analog Resolutions	1280x1024 @ 85Hz
	Maximum Number of Users	1
	MTBF	60,000 Hours
	On-Screen Display	Yes
	Pixel Pitch Support	0.297 x 0.297 mm
	Port Selection Support	Hotkeys and OSD (On Screen Display)
	Response Time	8ms
	Sync	45~80KHZ
	Viewing Angle	160° (H), 130° (V)
Connector(s)	Console Interface(s)	1 - USB A (4 pin) Female 1 - VGA (15 pin, High Density D-Sub) Female 2 - PS/2 (6 pin, Mini-DIN) Female
	OS Compatibility	OS independent; No software or drivers required
	Power	Input Voltage
Power Consumption (In Watts)		16
Power Source		Standard 120V Power Cords
Environmental	Operating Temperature	0°C to 50°C (32°F to 122°F)

	Storage Temperature	-20°C to 60°C (-4°F to 140°F)
Physical Characteristics	Color	Black
	Enclosure Type	Heavy Duty Steel
	Maximum Mounting Depth	31.5 in [800 mm]
	Minimum Mounting Depth	21.7 in [550 mm]
	Product Height	1.8 in [45 mm]
	Product Length	20.9 in [530 mm]
	Product Weight	24.3 lb [11 kg]
	Product Width	18.9 in [480.8 mm]
Packaging Information	Shipping (Package) Weight	36.7 lb [16.6 kg]
What's in the Box	Included in Package	1 - 1U LCD Rack Console Drawer (1)
		1 - Mounting Rails - Set (1)
		1 - Console Cable Kit (1)
		1 - Power Adapter (1)

Product appearance and specifications are subject to change without notice.