

16 Port Rackmount USB PS/2 Digital IP KVM Switch

StarTech ID: SV1641HDIE



This Digital IP KVM Switch offers secure and flexible local and remote administration of critical systems and services, combining our dependable Server Remote Control technology with a proven Enterprise-class digital KVM switch.

Server Remote Control

Unlike software solutions that require installation and work through your server operating system, this easy-to-configure IP KVM Switch delivers BIOS level control and full interaction with connected system boot processes over a TCP/IP connection. Users can reboot the system, access the BIOS and have full control over the keyboard and mouse as if they are on site - a cost-effective solution for outsourced server/IT hardware management and access to mission-critical corporate datacenter servers.

Built-in Security

Remote Control can't come at the expense of security! This Digital IP KVM switch features built-in support for SSH tunneling, SSL encryption and RADIUS authentication, as well as a configurable firewall. Plus, access to the IP KVM web console is user ID and SSL password secured to prevent unauthorized access.

A Scalable IP KVM Solution





A scalable KVM control solution, the IP KVM Switch supports up to 16 directly-connected servers or workstation computers. To create a more flexible infrastructure, the switch can be cascaded with other existing/new KVM switches for remote control of up to 136 computers from this single IP KVM unit.

To provide broader control options, the IP KVM switch supports modular integration, allowing you to add capability to your existing server remote control infrastructure. Using StarTech.com's <u>Serial Remote Control Module</u> (RPORT) for example, you can interact with virtually any device that uses a RS-232 serial terminal interface (network routers, switches, environmental controls, alarm systems etc.). Similarly, the IP KVM switch can be connected to StarTech.com's <u>8 Outlet Remote Power Switch</u> (PCM815SHNA) to power computers and equipment on and off using an interactive menu.

Versatile

Designed to accommodate a wide range of operating environments, the Digital IP KVM switch is compatible with PC, Mac and Sun Servers/Systems, ensuring the flexibility needed to efficiently manage connected devices regardless of operating platform.

To provide further versatility, the switch supports computers with USB or PS/2 keyboard and mouse connectors allowing a broader mix of connected computers including both legacy (PS/2) and modern (USB).

Rack Mounted Convenience

To preserve valuable server room or work space, the IP KVM can be mounted into 1U of rack/cabinet space. Similarly, all external connections to the server remote control/KVM unit are located on the rear panel to eliminate cable tangles and mess.



Applications

- Administer multiple servers for your Co-Location/ISP facility at the BIOS level either onsite or remotely saving time and money
- Create a scalable, streamlined access solution in your Datacenter or Server Farm
- Add to existing infrastructure, and access analog KVM switches via TCP/IP
- Perfect for use manufacturing line computer control, simplifying access to multiple systems
- Great for PC test/burn-in computer control saving the desk space required for multiple monitors, keyboards and mice
- Remote access for outsourced server / IT hardware management, saving travel time
- Remote access to mission-critical corporate datacenter servers ensuring maximum uptime

Features

- Allows remote reboot, BIOS access, and full control over keyboard and mouse as if they are on site
- Includes an onboard Web Server, providing browser-based configuration and administration.
- Supports 16 bit video
- Supports PCs with USB or PS/2 keyboard and mouse connectors
- No software or drivers required
- Login authentication restricts access to authorized users
- Plug and Play compliant
- Compact 1U rack height takes up very little cabinet or rack space
- Access to the web console is user ID and SSL password secure. The Remote Server Management over IP supports 32 user accounts and incorporates SSL encryption of session data, and SSL web communication encryption.
- Auto Scan Mode lets you switch between computers for easy monitoring
- Each computer name can be defined via the OSD menu
- Flash upgradeable
- Hot-pluggable feature allow computers to be added or removed without shutting down
- Hardware Reset and Network Configuration button
- Obtains an IP address using DHCP or manual configuration
- Universal KVM switch controls up to 16 computers directly and up to 136 computers by cascading 8 additional KVM switches
- Works with PC, Mac, Linux and Sun Systems
- Supports IntelliMouse (Pro)





Technical Specifications

Warranty 3 Years Enclosure Type Steel

Product Height 8.8 in [224.5 mm]
Product Length 15.9 in [404 mm]
Product Weight 146.5 oz [4150 g]
Product Width 1.7 in [43.2 mm]

Audio No
Cables Included No
Daisy-Chain Yes
KVM Ports 16
Multi-Monitor No

PC Interface USB and PS/2

PC Video Type VGA
Rack-Mountable Yes
DVI Support No
IP Control Yes

Maximum Cascaded 136

Maximum Analog

Resolutions

Computers

Maximum Digital

Resolutions

1600 x 1200 @ 85Hz

Maximum Number

of Users

1 active user plus up to 3 viewing

1920 x 1440 pixels local console

MTBF 876,000 Hours

OS Compatibility

OS independent; No software or drivers required

Note

Adding more than 1 optional PCM815SHNA power switch to the Server Remote Control requires a RPORT module.

Source code for the unit operating system is available upon request. Please contact us by phone, live chat, or email to make your request.

This offer is valid for three years from the date of purchase and/or for as long as parts or customer support is offered for this product.



Hard-to-find made easy®

Spec Sheet

Charges for the reasonable cost of copying and/or conveying may apply.

Center Tip Polarity Positive

Input Current 0.6A

Input Voltage 110 ~ 240 AC

Output Current 1.5A
Output Voltage 12 DC
Plug Type M

Power Source AC Adapter Included
Humidity Relative Humidity 95%

Operating 0 to +50°C

Temperature

Storage -20 to +60°C

Temperature

Shipping (Package) 9.7 lb [4.4 kg]

Weight

Included in Package 1 - 16 Port IP KVM Switch

Included in Package 1 - Mounting Brackets

Included in Package 1 - RS-232 Cable

Included in Package 1 - Bag, screws

Included in Package 1 - Pack, Rubber Feet

Included in Package 3 - Power Cords (NA/UK/EU)

Included in Package 1 - Power Adapter

Included in Package 1 - Instruction Manual

Certifications, Reports and Compatibility







