



CHANNEL

DB25F PIN-OUT VIEW

9

DB25F AND XLRM WIRING CHART										
XLR	XLR	CABLE	PIN 2	PIN 3	PIN 1					
(CHANNEL)	(DESC.)	(COLOR)	(RED)	(BLACK)	(BARE)					
1	XLRM	BROWN	24	12	25					
2	XLRM	RED	10	23	11					
3	XLRM	ORANGE	21	9	22					
4	XLRM	YELLOW	7	20	8					
5	XLRM	GREEN	18	6	19					
6	XLRM	BLUE	4	17	5					
7	XLRM	PURPLE	15	3	16					
8	XLRM	GRAY	1	14	2					

CUSTOMER DRAWING

NOTES:

- 1. BREAKOUT CABLE LENGTH: 18 +/- 0.75 INCHES. SEE TABLE FOR COLOR.
- (B) 2. THIS PRODUCT COMES COILED AND PACKAGED IN BAG.
- B 3. MATERIALS:
 XLR CONNECTORS:
 HANDLE ZINC ALLOY, NICKEL PLATED
 HOUSING AND LATCH ZINC ALLOY, NICKEL PLATED
 INSULATOR THERMOPLASTIC, GREEN
 PINS SPECIAL COPPER ALLOY, SILVER PLATED
 H.S. TUBING THERMOPLASTIC
 DSUB:
 CABLE CLAMP COPPER, NICKEL PLATED
 SHELL STEEL, TIN PLATED
 INSULATORS THERMOPLASTIC
 SCREW LOCKS BRASS, NICKEL PLATED

4. THIS PRODUCT IS RoHS COMPLIANT.

						THIS DRAWING DESCRIBES A DESIGN CONSIDERED PROPRIETARY IN NATURE, DEVELOPED AND MANUFACTURED BY SWITCHCRAFT INC. AND IS RELEASED ON A CONFIDENTIAL BASIS FOR IDENTIFICATION PURPOSES ONLY.							
					UNLESS OTHERWISE SPECIFIED	SIZE	W	/IDTH	MULT	LBS/I	Л	TEMPI	ER
					1. ALL DIMENSIONS IN INCHES [mm]	FINISH SPEC No.			MATERIAL				
					- TWO PLACE DECIMALS ±0.02 [0.5]					SPEC No.			
(27520	06/08/15	PC	TJK	- THREE PLACE DECIMALS ±0.005 [0.13]	FIRST USED ON DATE DRAWN BY CHKD		SCALE 1:2	 Swilteneral		⇒GT.®		
1	3 26637	10/4/10	RS	TJK									
	A 26568	7/20/10	RS	TJK		7/16/09	JGK	RS	TJK				
	A 26568	7/20/10	NO.	IJK				11/30/10	11/30/10	SHE	ET 1	OF	1
RI	EV ECO NUMBER	DATE	BY	APVD		NAME				PART No.			REV
REVISIONS			•	DO NOT SCALE DRAWING	DB25F TO 8-XLRM, RoHS DB25			5FXLF	₹M	C			

SolidWorks CAD File B