






RECOMMENDED CABLE: BELDEN B1505A

CRIMPED FERRULE HEX CRIMP SIZE .255 [6.48].

CRIMPED CONTACT PIN HEX CRIMP SIZE .042 [1.07].

ALTERNATE CONTACT PIN RADIAL CRIMP TOOL:
- DANIELS HAND TOOL NUMBER: MH992 OR MH995
- DANIELS POSTIONER NUMBER: K1803



NOTES:

1. BODY: COPPER ALLOY, NICKEL PLATED.
2. CONTACT PIN: COPPER ALLOY, GOLD PLATED.
3. SPRING: BERYLLIUM COPPER, NICKEL PLATED.
4. TINE CONTACT: BERYLLIUM COPPER, GOLD PLATED.
5. INSULATOR: TEFLON
6. FERRULE: COPPER ALLOY, NICKEL PLATED.
7. CHARACTERISTIC IMPEDANCE: 75 OHMS, 3 GHz BANDWIDTH.
8. RETURN LOSS: MEETS HDTV SMPTE 424M SPECIFICATION.
9. DIMENSIONS ARE FOR REFERENCE ONLY.
10. THIS PRODUCT IS RoHS COMPLIANT.

RECOMMENDED CABLE STRIPPING AND CRIMPING DIMENSIONS

CUSTOMER DRAWING

					THIS DRAWING DESCRIBES A DESIGN CONSIDERED PROPRIETARY IN NATURE, DEVELOPED AND MANUFACTURED BY SWITCHCRAFT INC. AND IS RELEASED ON A CONFIDENTIAL BASIS FOR IDENTIFICATION PURPOSES ONLY.				
					SIZE *	WIDTH *	MULT *	LBS/M *	TEMPER *
					FINISH *	MATERIAL SEE NOTES			
					SPEC No. *	SPEC No. *			
					FIRST USED ON *	SCALE 4:1			
					DATE DRAWN	BY	CHKD	APVD	
					04/29/10	ZS	04/29/10	04/29/10	
							SRC	SRC	
					NAME			PART No.	REV
					DIN 1.0/2.3 PLUG, 75 OHMS, RoHS			DIN1505A	B