



RECOMMENDED
PANEL CUT-OUT

CUSTOMER DRAWING

- NOTES:
1. INSERTION LOSS: 1.0 dB MAX.
 2. MATERIALS:
HOUSING - DELRIN, BLACK
TOSLINK ADAPTER - ABS
CENTER PIN - BRASS, GOLD PLATED
DUST CAPS - PVC
 3. FOR SCREWS TO BE SHIPPED WITH ASSEMBLY AND INDIVIDUAL PACKAGING, ADD SUFFIX -PKG TO PART NUMBER.
 4. WHEN MOUNTING ASSEMBLY, USE A SCREW TORQUE OF 10 INCH-POUNDS MAXIMUM.
 5. THIS PRODUCT IS RoHS COMPLIANT.

					<div>UNLESS OTHERWISE SPECIFIED</div> <div>1. ALL DIMENSIONS IN INCHES</div> <div>- TWO PLACE DECIMALS ±0.02</div> <div>- THREE PLACE DECIMALS ±0.005</div>	THIS DRAWING DESCRIBES A DESIGN CONSIDERED PROPRIETARY IN NATURE, DEVELOPED AND MANUFACTURED BY SWITCHCRAFT INC. AND IS RELEASED ON A CONFIDENTIAL BASIS FOR IDENTIFICATION PURPOSES ONLY.									
						SIZE	WIDTH		MULT		LBS/M		TEMPER		
						FINISH					MATERIAL				
						SPEC No.					SEE NOTES				
						FIRST USED ON			SCALE		Switchcraft®				
									3:2						
B	26950	5-7-12	TO	TJK		DATE DRAWN	BY	CHKD	APVD		SHEET 1 OF 1				
A	26347	2/26/09	RS	TJK		5/12/08	JGK	RS	TJK						
								6/8/09	7/20/09						
REV	ECO NUMBER	DATE	BY	APVD		NAME					PART No.		REV		
REVISIONS					DO NOT SCALE DRAWING	E SERIES TOSLINK ADAPTER, RoHS					EHTL2		B		

SolidWorks CAD File

