

1T-PC-1280HD Video Scaler is a Cross Converter for PC and HD formats and resolutions. The input resolution is automatically detected and can either be RGBHV, YPbPr or YUV format. Output Resolutions up to 1920x1200 and 1080p are accommodated. In addition to converting between PC and HD, the unit can take a 480i Component Video signal (from a DVD Player for example) and convert it to PC or HD resolutions. The output resolution and refresh rate is selected via push buttons or an On Screen Display. The integral processor provides control over many signal parameters, such as: Contrast, Brightness, Color Saturation, R-G-B Levels and H-V Positioning.

The unit is 12VDC powered and the Power Adapter is included featuring locking DC Connectors for security.



Key Features of the Cross Converter-Scaler

- Ultra Compact, High Performance Unit
- Cross Convert between PC and HD resolutions
- PC Output Resolutions up to 1920x1200
- HD Output Resolutions up to 1080p
- Locking DC Power Connector for Security

Specifications

I/O Resolutions		
VESA	Resolution	Refresh Rate
VGA	640x480	RGBHV 60, 72, 75, 85Hz
VGA70	720x400	RGBHV 70Hz
VESA85	640x400	RGBHV 85Hz
SVGA	800x600	RGBHV 60, 72, 75, 85Hz
XGA	1024x768	RGBHV 60, 70, 75, 85Hz
Mac	1152x864	RGBHV 70, 75Hz
WXGA	1280x768	RGBHV 60Hz
1280A	1280x960	RGBHV 60Hz
SXGA	1280x1024	RGBHV 60, 75Hz
UXGA	1600x1200	RGBHV 60Hz (Out Only)
WUXGA	1920x1200	RGBHV 50, 60Hz (Out Only)
480i	720x480 NTSC	(i) RGBHV, YUV 60Hz (In Only)
576i	720x576 PAL	(i) RGBHV, YUV 50Hz (In Only)
1080i	1920x1080	(i) RGBHV, YPbPr 50, 60Hz (i) (Note 1)
480p	720x480	RGBHV, YPbPr 60Hz
576p	720x576	RGBHV, YPbPr 50Hz
720p	1280x720	RGBHV, YPbPr 50, 60Hz (Note 2)
1080p	1920x1080	RGBHV, YPbPr 50, 60Hz (Out Only) (Note 2)
Input		
RGBHV, YPbPr, YUV		1x via HD-15 Connector
Output		
RGBHV, YPbPr		1x via HD-15 Connector

Picture Controls	
Input Signal	Clock Frequency, Phase
Output Signal	Brightness, Contrast, Color, R-G-B Levels, H&V Position
Mechanical	
Size (H-W-D)	30x133x76mm (1.2"x5.25"x3")
Weight (Net)	280 g (0.62lbs)
Warranty	
Limited Warranty	3 Years Parts and Labor
Environmental	
Operating Temperature	0° to +50° C (+32° to +122° F)
Operating Humidity	10% to 90%, Non-condensing
Storage Temperature	-10° to +60° C (+14° to +140° F)
Storage Humidity	10% to 90%, Non-condensing
Power Requirement	
External Power Supply	12VDC@1A – Locking DC
Regulatory Approvals	
Amplifier Units	FCC, CE, RoHS
Power Supplies	UL, CUL, CE, PSE, GS, RoHS
Accessories Included	
1x Power Adapter	US, UK or Euro
1x Operations Manual	
Notes	
(1) The 1080i signal is actually a doubled 540p signal which is recognized as a 1080i signal by most HDTV displays.	
(2) YPbPr is available on Output Only; Input is RGBHV Only	

Panel Drawings

