

---

# ***RTS***

---



RTS Headsets

---

# Earsets

The popular RTS earsets are precisely designed for inconspicuous listening while on camera. Used by nearly all major television networks and stations, we have surpassed industry standards. The extremely efficient miniature driver element requires only nominal operating power and enables the announcer to hear program cues while working with a live microphone. The units are also suitable for many other applications such as live theater script prompting.

## Typical Set-Up

To provide optimum versatility, the announcer's earset is made up of interchangeable components that simply snap together. Users can construct a version of the announcer's earset that best suits their particular needs. Some popular combinations are available as a standard configuration; these are listed below.



## Complete Earsets



|                          |      |
|--------------------------|------|
| Earsets                  | 2-3  |
| Lightweight              | 4-5  |
| Premium<br>Lightweight   | 6-7  |
| Medium Weight            | 8-11 |
| Monitor                  | 12   |
| Under Helmet             | 13   |
| Headset &<br>Accessories | 14   |
| Specs                    | 15   |

## Telethin® Magnetic Receivers

Telethin Magnetic Receivers, available in 4 different impedances, permits choice of impedance for any application. For inconspicuous use, the receiver is extremely small and lightweight.

|                                                                                     |                         |
|-------------------------------------------------------------------------------------|-------------------------|
|  | <b>RTR-04</b> 15 Ohms   |
|                                                                                     | <b>RTV-04</b> 125 Ohms  |
|                                                                                     | <b>RTW-04</b> 500 Ohms  |
|                                                                                     | <b>RTX-04</b> 1000 Ohms |
|                                                                                     | <b>RTY-04</b> 2000 Ohms |

## Standard Telethin® Cord Sets

The standard earset system comes equipped with a 5', low luster gray or beige cord with a 1/4" connector. A variety of other cords with or without volume controls are available as components.



**CMT-95**  
Straight cord with sub-miniature straight connector



**CMT-98**  
Straight cord with straight miniature connector



**CMT-2**  
Straight cord with sub-miniature straight connector



**CMT-92**  
Straight cord with right angle miniature connector



**CCX-2**  
Coiled cord with right angle miniature connector



**CCT-2**  
Coiled extended cord with 1/4" connector

## Earmolds/Earcones/Eartips

For maximum comfort and convenience, three pliable earmolds (S, M & L) are available for either the left or right ear. The Telethin receiver easily attaches into the earpiece directing sound into the ear canal and limiting ambient noise.

### Earmolds



**EML-1R**  
Large, right ear  
**EML-2L**  
Large, left ear



**EMM-1R**  
Medium, right ear  
**EMM-2L**  
Medium, left ear



**EMS-1R**  
Small, right ear  
**EMS-2L**  
Small, left ear



### Earcones

**BT-4**  
Bag of 5 large earcones for use with ET-4



**BT-3**  
Bag of 5 medium earcones for use with ET-4



**BT-2**  
Bag of 5 small earcones for use with ET-4

### Eartips



**ET-1**  
Eartip, soft silicone tip, salmon colored, with metal plug



**BT-1**  
Bag of 25 replacement eartips, salmon colored, for use with ET-1

## Cords

The cords with in-line volume control are equipped with clothing clips for out of sight, waist-level positioning. To avoid loss of cues, the volume control will not shut off completely.



**VXT-3** 500 Ohm volume control with 1/4" connector



**VYT-3** 2000 Ohm volume control with 1/4" connector

## Eartubes

These inconspicuous clear plastic tubes carry the sound effectively from a RTS Telethin receiver to the talent's ear without revealing the cord to the camera. The clear tubes are available in 3 versions. All connect easily to a RTS eartip, earcone or any size earmold and have a handy clothing clip to secure the system in place.



**ET2** Coiled acoustic eartube with clothing clip for use with earmolds or eartip



**ET4** Coiled acoustic eartube with clothing clip for use with earcones – comes with one each – S, M & L earcones



**ET3** Straight acoustic eartube with clothing clip for use with earmolds or eartip

## Earloops

The nylon or plastic covered metal earloop holds the eartip or receiver in place on the ear.



**AEF-3**  
Nylon earloop



**AEF-2**  
Plastic covered metal earloop

## Earsset components (not shown)

**AFC-1** Under-chin tube and foam cushion

# Lightweight Headsets

The RTS lightweight headsets provide users with an ideal combination of functionality and comfort. The PH-44 and PH-88 models offer users an efficient and durable standard headset while the MH models accommodate the needs of those who are looking for the added features of a premium headset.



## **PH-44**

The PH-44 headset is a super lightweight, dual-sided headset for the ultimate in day-long comfort. The PH-44 features high quality dynamic earphones with a dynamic noise-cancelling microphone with a semi-rigid, fully adjustable boom for precise positioning. The high-quality wide band dynamic earphones offer a better fit, isolation, and frequency response. Additional versions are available including 4 or 5 pin male or female XLR connectors.

## PH-88

The PH-88 headset is a super lightweight, single-sided headset for the ultimate in day long comfort. The PH-88 features high quality dynamic earphones with a dynamic-noise cancelling microphone with a semi-rigid, fully adjustable boom for precise positioning. The high-quality wide band dynamic earphones offer a better fit, isolation, and frequency response. Additional versions are available including 4 or 5 pin male or female XLR connectors.



## Premium Lightweight Headsets



### **MH-402**

The MH-402 dual-sided ANR (Active Noise Reduction) headset provides the newest design in headset technology from RTS. The battery-powered Active Noise Reduction system targets noise in the environment and drastically reduces it, allowing for clear and precise communications. The modular design allows you to interchange modules to allow for the best headset configuration for any environment. The noise-cancelling microphone, combined with the headphone transducers, provide clear and precise communication in noisy environments. Finally, this headset is not limited to live studio or venue communications. By installing the appropriate module, you can connect to an MP3 player or many other types of audio devices.



## MH-302

The MH-302 is designed with you, the user, in mind. The headset features a durable modular design, lightweight construction, installation options and multi-functional use. The modular design allows you to interchange modules for any environment. The noise-cancelling microphone, combined with the headphone transducers, provide clear communication in noisy environments. Finally, this headset is not limited to live studio or venue communications. By installing the appropriate module, you can connect to an MP3 player or many other types of audio devices. The MH Series Headsets provide clear communications for professional applications including live remote or studio broadcasting, film, TV, or theater intercom communications.



## MH-300

The MH-300 single-sided headset provides the newest design from RTS. It features a rugged, modular design, lightweight construction, installation options, and multiple functions beyond the live studio or theater venue. The modular design allows you to interchange modules to allow for the best headset configuration for any environment. The noise-cancelling microphone, combined with the headphone transducers, provide clear and precise communication in noisy environments. Finally, by installing the appropriate module, you can connect to any audio device.

## Medium Weight Headsets

The PH Series of medium-weight intercom headsets is considered the industry standard by many users in all different applications. The PH Series features both durability and functionality. With weights between 11-13 oz., these headsets offers the ultimate in day-long comfort.



### **PH-1**

The PH-1 is a medium-weight single-sided headset with foam-filled cushions that offer a light feel with moderate isolation from ambient noise. The dynamic noise-cancelling mic is easily positioned with a unique ball joint for continuous adjustability. Available with 4 or 5 pin male or female XLR connectors. Additional versions are available including 4 or 5 pin male or female XLR connectors.



## PH-2

The PH-2 headset is a medium weight, full cushion, dual-sided headset for the ultimate in day long comfort. The headset has foam-filled cushions that offer a light feel with moderate isolation from ambient noise. The PH-2 features a high quality monaural dynamic earphone with a dynamic noise-cancelling microphone on an adjustable ball joint boom that can be positioned on either side of the head. Versions are available with 4 pin male or female connectors.



## PH-3

The PH-3 is a medium-weight dual-sided stereo headset with foam-filled cushions that offer a light feel with moderate isolation from ambient noise. The dynamic noise-cancelling mic is easily positioned with a unique ball joint for continuous adjustability. Versions are available with 4 pin male or female connectors.

## Medium Weight Headsets

The HR Series of medium-weight intercom headsets features a unique design that is both comfortable and functional. The HR Series provides users with a premium headset option loaded with features. The earcup and ergonomically designed headband provide added comfort through 3 unique pressure settings combined with a moleskin covered headband and earmuffs. This design also provides 21dB of passive hearing protection. The cord comes terminated in either 4 or 5 pin XLR, male or female and can also be purchased unterminated for custom applications.



### **HR-1**

The HR-1 is a single muff, medium-weight passive noise reduction headset with a dynamic noise-cancelling microphone. The ergonomic headband design distributes the ear cushion pressure evenly over the entire ear with no pressure points, ensuring hours of comfortable wear. An added advantage of this headset design is that it folds into compact form for ease of transport and storage. Additional versions are available including 4 or 5 pin male or female XLR connectors.

## HR-2

The HR-2 is a dual-sided, medium-weight passive noise reduction headset with a dynamic noise-cancelling microphone. The headset has a noise reduction rating of 21dB; suitable for use in a moderately noisy environment. The HR-2 features our unique, soft padded headband for day-long comfort. Our ergonomic headset design distributes ear cushion pressure evenly over the entire ear with no pressure points, unlike conventional headsets. An added advantage of this headset design is that it folds into compact form for ease of transport and storage. Additional versions are available including 4 or 5 pin male or female XLR connectors.



# Monitor Headphones

## HFY-91

The HFY-91 is an under-the-chin style headphone terminated with a ¼" phone plug.



## PH-36

The PH-36 is a lightweight, dual-sided mono headphone with a ¼" plug.



## HR-1L

The HR-1L & HR-2L are medium-weight, noise reduction headsets with dynamic microphones. The HR-1L is a single-sided headset while the HR-2L is a dual-sided headset. The headsets effectively reduce noise and are suitable for use in moderately noisy environments. All models feature a unique, soft padded headband design that distributes ear cushion pressure evenly over the entire ear with no pressure points, unlike conventional designs which apply more pressure on the bottom of the ear than the top. An added advantage of this design is that the headset folds into an extremely compact shape.



# Under Helmet

## PH-16

The PH-16 is a monaural headset with a noise-cancelling dynamic microphone. The PH-16 is designed to fit under a helmet with an environmental protection agency noise reduction rating (NRR) of 24dB. The headset cord is terminated with a 4-pin XLR female connector. The dynamic receivers have special mounting which resist shock, vibration, and acoustic feedback. The PH-16 ear cups are foam lined for added noise attenuation. The vented, foam-filled ear cushions combine comfort with good acoustic seal. For convenience and economy, the receivers and ear cushions are field repairable.



## HS-6A

The HS-6A is a telephone-style handset that offers a push-to-talk switch, dynamic earphone and dynamic microphone. It is supplied with a metal hanger bracket for vertical storage and is compatible with most user stations. The HS-6A is terminated with an A4F plug. Available in white or black.



### Headset Accessories

| Model  | Description            |
|--------|------------------------|
| CC-1   | Cover Cushion CC-1     |
| C2     | C2 Ear Cushion, Gray   |
| C3     | C3 Ear Cushion, Black  |
| C-4    | Cushion, Ear           |
| C-5    | Ear Cushion            |
| C-8    | Ear-Cushion            |
| WS-2   | Windscreen Accessory   |
| WS-2B  | Windscreen             |
| WS-3   | Windscreen Pkgd        |
| PT-400 | Ptt Kit Locking        |
| AEF-3B | Nylon Earloop, Clear   |
| ET-1B  | Eartip, Salmon Colored |
| HE-15  | Extension Cable        |
| HE-30  | Extension Cable        |

### MH Headset Accessories

| Model     | Description                          |
|-----------|--------------------------------------|
| MH-EC     | MH ACC Ear Cushion                   |
| MH-WC     | MH ACC Dyn Mic Windscreen            |
| MH-BAT    | MH ACC Lion Battery                  |
| MH-BC     | MH ACC Battery Charger w/Adapters    |
| MH-BCA    | MH ACC Power Supply Adapters         |
| MH-AAM    | MH ACC Aux Audio Module              |
| MH-DMM-QC | MH ACC Dyn Mic Module, Quick Connect |
| MH-QC-A4M | MH ACC Quick Connect –A4M            |
| MH-QC-A4F | MH ACC Quick Connect-A4F             |
| MH-QC-A5M | MH ACC Quick Connect-A5M             |
| MH-QC-A5F | MH ACC Quick Connect-A5F             |
| MH-FM     | MH ACC Filler Module                 |
| MH-TP     | MH ACC Temple Pad                    |
| MH-CC     | MH ACC Carry Case                    |
| MH-DM-A4M | MH ACC Dyn Module-A4M                |
| MH-DM-A4F | MH ACC Dyn Module-A4F                |
| MH-DM-A5M | MH ACC Dyn Module-A5M                |
| MH-DM-A5F | MH ACC Dyn Module-A5F                |



| Model Name | Type              | Mic Sensitivity | Mic Frequency Range | Mic Impedance | Speaker Sensitivity  | Speaker Frequency Range | Speaker Impedance | Connector Termination                                                              | Cord Length                       | Weight (not including cord) |
|------------|-------------------|-----------------|---------------------|---------------|----------------------|-------------------------|-------------------|------------------------------------------------------------------------------------|-----------------------------------|-----------------------------|
| PH-88      | Single Sided      | -65dBV/Pa @1cm  | 200Hz - 10kHz       | 200ohm        | 109dB SPL @1kHz, 1mW | 100Hz - 7kHz            | 300ohm            | XLR 4-pin Female                                                                   | 5.5 ft./1.6m                      | 2.5oz./70.8g                |
| PH-88R     | Single Sided      | -65dBV/Pa @1cm  | 200Hz - 10kHz       | 200ohm        | 109dB SPL @1kHz, 1mW | 100Hz - 7kHz            | 300ohm            | XLR 4-pin Male                                                                     | 5.5 ft./1.6m                      | 2.5oz./70.8g                |
| PH-88R5    | Single Sided      | -65dBV/Pa @1cm  | 200Hz - 10kHz       | 200ohm        | 109dB SPL @1kHz, 1mW | 100Hz - 7kHz            | 300ohm            | XLR 5-pin Male                                                                     | 5.5 ft./1.6m                      | 2.5oz./70.8g                |
| PH-88E     | Single Sided      | -65dBV/Pa @1cm  | 200Hz - 10kHz       | 200ohm        | 109dB SPL @1kHz, 1mW | 100Hz - 7kHz            | 300ohm            | XLR 4-pin Female coiled cord                                                       | 2 ft./ .6m<br>12 ft./3.6 extended | 2.5oz./70.8g                |
| PH-8S      | Single Sided      | -65dBV/Pa @1cm  | 200Hz - 10kHz       | 200ohm        | 109dB SPL @1kHz, 1mW | 100Hz - 7kHz            | 300ohm            | 3.5mm 4-conductor                                                                  | 9 ft./2.7m                        | 2.5oz./70.8g                |
| PH-44      | Dual Sided Mono   | -65dBV/Pa @1cm  | 200Hz - 10kHz       | 200ohm        | 109dB SPL @1kHz, 1mW | 100Hz - 7kHz            | 150ohm            | XLR 4-pin Female                                                                   | 5.5 ft./1.6m                      | 3oz./85g                    |
| PH-44R     | Dual Sided Mono   | -65dBV/Pa @1cm  | 200Hz - 10kHz       | 200ohm        | 109dB SPL @1kHz, 1mW | 100Hz - 7kHz            | 150ohm            | XLR 4-pin Male                                                                     | 5.5 ft./1.6m                      | 3oz./85g                    |
| PH-44A5    | Dual Sided Stereo | -65dBV/Pa @1cm  | 200Hz - 10kHz       | 200ohm        | 109dB SPL @1kHz, 1mW | 100Hz - 7kHz            | 300ohm per side   | XLR 5-pin Female                                                                   | 5.5 ft./1.6m                      | 3oz./85g                    |
| PH-44R5    | Dual Sided Stereo | -65dBV/Pa @1cm  | 200Hz - 10kHz       | 200ohm        | 109dB SPL @1kHz, 1mW | 100Hz - 7kHz            | 300ohm per side   | XLR 5-pin Male                                                                     | 5.5 ft./1.6m                      | 3oz./85g                    |
| PH-44R6    | Dual Sided Stereo | -65dBV/Pa @1cm  | 200Hz - 10kHz       | 200ohm        | 109dB SPL @1kHz, 1mW | 100Hz - 7kHz            | 300ohm per side   | XLR 6-pin Male                                                                     | 5.5 ft./1.6m                      | 3oz./85g                    |
| PH-44PT    | Dual Sided        | -65dBV/Pa @1cm  | 200Hz - 10kHz       | 200ohm        | 109dB SPL @1kHz, 1mW | 100Hz - 7kHz            | 300ohm per side   | Stripped wire                                                                      | 5.5 ft./1.6m                      | 3oz./85g                    |
| PH-88-IC3  | Single Sided      | -65dBV/Pa @1cm  | 200Hz - 10kHz       | 200ohm        | 109dB SPL @1kHz, 1mW | 100Hz - 7kHz            | 300ohm            | Dual 3.5mm                                                                         | 9 ft./2.7m                        | 2.5oz./70.8g                |
| PH-44-IC3  | Dual Sided Mono   | -65dBV/Pa @1cm  | 200Hz - 10kHz       | 200ohm        | 109dB SPL @1kHz, 1mW | 100Hz - 7kHz            | 150ohm            | Dual 3.5mm                                                                         | 9 ft./2.7m                        | 3oz./85g                    |
| PH-1       | Single Sided      | -65dBV/Pa @1cm  | 200Hz - 6kHz        | 150ohm        | 95dB SPL @1kHz, 1mW  | 100Hz - 10kHz           | 300ohm            | XLR 4-pin Female                                                                   | 5.5 ft./1.6m                      | 11oz./311.8g                |
| PH-1R      | Single Sided      | -65dBV/Pa @1cm  | 200Hz - 6kHz        | 150ohm        | 95dB SPL @1kHz, 1mW  | 100Hz - 10kHz           | 300ohm            | XLR 4-pin Male                                                                     | 5.5 ft./1.6m                      | 11oz./311.8g                |
| PH1-R5     | Single Sided      | -65dBV/Pa @1cm  | 200Hz - 6kHz        | 150ohm        | 95dB SPL @1kHz, 1mW  | 100Hz - 10kHz           | 300ohm            | XLR 5-pin Male                                                                     | 5.5 ft./1.6m                      | 11oz./311.8g                |
| PH1-1PT    | Single Sided      | -65dBV/Pa @1cm  | 200Hz - 6kHz        | 150ohm        | 95dB SPL @1kHz, 1mW  | 100Hz - 10kHz           | 300ohm            | Stripped wire                                                                      | 5.5 ft./1.6m                      | 11oz./311.8g                |
| PH-2       | Dual Sided Mono   | -65dBV/Pa @1cm  | 200Hz - 6kHz        | 150ohm        | 95dB SPL @1kHz, 1mW  | 100Hz - 10kHz           | 150ohm            | XLR 4-pin Female                                                                   | 5.5 ft./1.6m                      | 13oz./368.5g                |
| PH-2R      | Dual Sided Mono   | -65dBV/Pa @1cm  | 200Hz - 6kHz        | 150ohm        | 95dB SPL @1kHz, 1mW  | 100Hz - 10kHz           | 150ohm            | XLR 4-pin Male                                                                     | 5.5 ft./1.6m                      | 13oz./368.5g                |
| PH-2PT     | Dual Sided        | -65dBV/Pa @1cm  | 200Hz - 6kHz        | 150ohm        | 95dB SPL @1kHz, 1mW  | 100Hz - 10kHz           | 300ohm per side   | Stripped wire                                                                      | 5.5 ft./1.6m                      | 13oz./368.5g                |
| PH-3       | Dual Sided Stereo | -65dBV/Pa @1cm  | 200Hz - 6kHz        | 150ohm        | 95dB SPL @1kHz, 1mW  | 100Hz - 10kHz           | 300ohm per side   | XLR 5-pin Female                                                                   | 5.5 ft./1.6m                      | 13oz./368.5g                |
| PH-3R5     | Dual Sided Stereo | -65dBV/Pa @1cm  | 200Hz - 6kHz        | 150ohm        | 95dB SPL @1kHz, 1mW  | 100Hz - 10kHz           | 300ohm per side   | XLR 5-pin Male                                                                     | 5.5 ft./1.6m                      | 13oz./368.5g                |
| MH-300     | Single Sided      | -65dBV/Pa @1cm  | 200Hz - 10kHz       | 200ohm        | 100dB SPL @1kHz, 1mW | 100Hz - 10kHz           | 150ohm            | MH Series headsets are available in 4 or 5 pin, male or female, XLR configurations | 5.9 ft./1.7m                      | 8oz./226.7g                 |
| MH-302     | Dual Sided        | -65dBV/Pa @1cm  | 200Hz - 10kHz       | 200ohm        | 100dB SPL @1kHz, 1mW | 100Hz - 10kHz           | 150ohm            |                                                                                    | 5.9 ft./1.7m                      | 10oz./283.5g                |
| MH-402     | Dual Sided ANR    | -65dBV/Pa @1cm  | 200Hz - 10kHz       | 200ohm        | 100dB SPL @1kHz, 1mW | 100Hz - 10kHz           | 150ohm            |                                                                                    | 5.9 ft./1.7m                      | 10oz./283.5g                |
| HR-1       | Single Sided      | -65dBV/Pa @1cm  | 150Hz - 8kHz        | 200ohm        | 95dB SPL @1kHz, 1mW  | 100Hz - 3kHz            | 300ohm            | XLR 4-pin Female                                                                   | 5 ft./1.5m                        | 11oz./311.8g                |
| HR-1R      | Single Sided      | -65dBV/Pa @1cm  | 150Hz - 8kHz        | 200ohm        | 95dB SPL @1kHz, 1mW  | 100Hz - 3kHz            | 300ohm            | XLR 4-pin Male                                                                     | 5 ft./1.5m                        | 11oz./311.8g                |
| HR-1R5     | Single Sided      | -65dBV/Pa @1cm  | 150Hz - 8kHz        | 200ohm        | 95dB SPL @1kHz, 1mW  | 100Hz - 3kHz            | 300ohm            | XLR 5-pin Male                                                                     | 5 ft./1.5m                        | 11oz./311.8g                |
| HR-1PT     | Single Sided      | -65dBV/Pa @1cm  | 150Hz - 8kHz        | 200ohm        | 95dB SPL @1kHz, 1mW  | 100Hz - 3kHz            | 300ohm            | Stripped wire                                                                      | 5 ft./1.5m                        | 11oz./311.8g                |
| HR-2       | Dual Sided Mono   | -65dBV/Pa @1cm  | 150Hz - 8kHz        | 200ohm        | 95dB SPL @1kHz, 1mW  | 100Hz - 3kHz            | 150ohm            | XLR 4-pin Female                                                                   | 5 ft./1.5m                        | 15oz./425.2g                |
| HR-2R      | Dual Sided Mono   | -65dBV/Pa @1cm  | 150Hz - 8kHz        | 200ohm        | 95dB SPL @1kHz, 1mW  | 100Hz - 3kHz            | 150ohm            | XLR 4-pin Male                                                                     | 5 ft./1.5m                        | 15oz./425.2g                |
| HR-2R5     | Dual Sided Stereo | -65dBV/Pa @1cm  | 150Hz - 8kHz        | 200ohm        | 95dB SPL @1kHz, 1mW  | 100Hz - 3kHz            | 300ohm per side   | XLR 5-pin Male                                                                     | 5 ft./1.5m                        | 15oz./425.2g                |
| HR-2A5     | Dual Sided Stereo | -65dBV/Pa @1cm  | 150Hz - 8kHz        | 200ohm        | 95dB SPL @1kHz, 1mW  | 100Hz - 3kHz            | 300ohm per side   | XLR 5-pin Female                                                                   | 5 ft./1.5m                        | 15oz./425.2g                |
| HR-2PT     | Dual Sided        | -65dBV/Pa @1cm  | 150Hz - 8kHz        | 200ohm        | 95dB SPL @1kHz, 1mW  | 100Hz - 3kHz            | 300ohm per side   | Stripped wire                                                                      | 5 ft./1.5m                        | 15oz./425.2g                |
| HR-1L      | Single Sided      | N/A             | N/A                 | N/A           | 95dB SPL @1kHz, 1mW  | 100Hz - 3kHz            | 300ohm            | Stripped wire                                                                      | 5 ft./1.5m                        | 15oz./425.2g                |
| HR-2L      | Dual Sided        | N/A             | N/A                 | N/A           | 95dB SPL @1kHz, 1mW  | 100Hz - 3kHz            | 300ohm per side   | Stripped wire                                                                      | 5 ft./1.5m                        | 15oz./425.2g                |
| PH-36      | Dual Sided Mono   | N/A             | N/A                 | N/A           | 109dB SPL @1kHz, 1mW | 100Hz - 7kHz            | 150ohm            | 1/4" plug                                                                          | 5.5 ft./1.6m                      | 3oz.                        |
| PH-16      | Dual Sided Mono   | -65dBV/Pa @1cm  | 200Hz - 6kHz        | 150ohm        | 93dB SPL @1kHz, 1mW  | 100Hz - 3kHz            | 150ohm            | XLR 4-pin Female                                                                   | 5.5 ft./1.6m                      | 15oz./425.2g                |
| PH-16R     | Dual Sided Mono   | -65dBV/Pa @1cm  | 200Hz - 6kHz        | 150ohm        | 93dB SPL @1kHz, 1mW  | 100Hz - 3kHz            | 150ohm            | XLR 4-pin Male                                                                     | 5.5 ft./1.6m                      | 15oz./425.2g                |
| PH-16R5    | Dual Sided Stereo | -65dBV/Pa @1cm  | 200Hz - 6kHz        | 150ohm        | 93dB SPL @1kHz, 1mW  | 100Hz - 3kHz            | 300ohm per side   | XLR 5-pin Male                                                                     | 5.5 ft./1.6m                      | 15oz./425.2g                |

*All products except Monitor Headphones feature a dynamic noise-cancelling microphone*



For information on any of the products featured in this catalog, you can reach us at [info@rtsintercoms.com](mailto:info@rtsintercoms.com)  
Please visit the RTS Digital Matrix Intercom website at: [www.rtsintercoms.com](http://www.rtsintercoms.com)

---

## **Americas**

Bosch Communications Systems  
RTS Communications Inc.  
12000 Portland Ave South,  
Burnsville, MN 55337, USA  
USA—Phone: 877-863-4169, Fax: 1-800-955-6831  
Canada—Phone: 1-866-505-5551, Fax: 1-866-336-8467  
Latin America—Phone: +55 19 2103-2860, Fax: +55 19 2103-2860

## **Europe, Africa & Middle-East**

EVI Audio GmbH.  
Sachsen Ring 60  
94315  
Straubing, Germany  
Phone: +49 9421 706-0, Fax: +49 9421 706-265  
UK: RTS Communications (U.K.), Ltd.,  
Broadwater Park  
Willow Lane, Mitcham  
Denham UB9 5HJ GB  
Phone: +44 1707 280 960, Fax: +44 1707 265 083

## **Asia & Pacific Rim**

Japan: EVI Audio Japan Ltd.  
5-3-8 Funabashi, Setagaya-Ku,  
Tokyo, Japan 156-0055  
Phone: +81 3-5316-5020, Fax: +81-3-5316-5030  
  
China: EVI Audio Ltd.  
Room 2210-2215, Tower B, Far East International  
Plaza, No. 317, Xianxia Road,  
Shanghai, China, Post Code: 200051  
Phone: +86 (21) 6235-1677, Fax: +86 (21) 6235-1676  
  
Hong Kong: EVI Audio (HK) Ltd.  
7th Floor China Minmetals Tower,  
No. 79 Chatham Road South,  
Tsim Sha Tsui, Kowloon, HK  
Phone: +852 2351-3628, Fax: +852 2351-3329  
  
Singapore: Bosch Communications Systems  
RTS Communications (SEA) Pte Ltd  
38C Jalan Pemimpin  
Singapore 577180  
Phone: +(65) 6319 0621, Fax: +(65) 6319 0620