

Eight HD-SDI Fiber Transport Kit with Dual Aux Ports

Single fiber transport for SDI video, audio, serial data, & contact closure



The F-M8SDI fiber link provides 8 full rate HD-SDI signals, return path RS-485, and two optional auxiliary ports that can be custom ordered to support analog audio, RS-232/422, or contact closure circuits. All transported over a single fiber strand.

The standard unit without options provides one directional RS-485 data from the receiver unit to the transmitter. This can be used for control applications such as PTZ controllers or video switches. This also allows a return path that provides a link alarm indicator on both units that indicates when an optical link is not present. Each aux option must be ordered at the time of purchase, and the units cannot be converted from one option to the other. Consult a sales representative for more details.

Product Specifications and Information Table

HD-SDI Interface		RS485 Interface	
Connectors	8x BNC	Connector	Terminal Block connector
Bit rate	1.485Gb/s	Baud rate	0 ~ 115.2Kb/s
Impedance	75Ω	Bit error ratio	<10 ⁻⁹
Return loss	>15dB	Duplex	Half-duplex
Output level	800mVp-p±10%	Power Consumption	
Rise and fall time (HD-SDI)	≤270ps	Power supply	DC 12V
HD-SDI Alignment jitter (100KHz)	≤0.2UI	DC input voltage range	8V~14V
HD-SDI Timing jitter (10Hz)	<1.0UI	Power consumption	3W±10%
Standard	SMPTE-292M HD-SDI	Environmental	
Audio Interface (Optional)		Working temperature	-30 ~ 60°C
Connector	Terminal Block	Relative Humidity	≤95%, no condensation
Impedance	high-impedance 600Ω	Storage temperature	-40 ~ 85°C
Bandwidth	20Hz~20KHz	Dimensions	
Total Harmonic Distortion	0.1%	1RU Enclosure	180mm x 123mm x 30mm