

## LCD-1701TSL - Front



## LCD-1701TSL - Flush Mount Monitor

This high performance touch screen monitor is made for use in a 24/7 environment; ideal for monitor station security surveillance, and AV applications.

### Benefits

Very wide viewing angle (85/85/85/85)  
4:3 native aspect ratio  
Can function between 50° – 104°F  
Built-in speakers

### Related Products

LCD-1701TS

## LCD-1701TSL - Back



Specifications	
Mount	Flush
Anti Glare Coating	Yes
Case	Metal
Native Aspect Ratio	4:3
Visible Screen Size (WH)	338 x 270 mm / 13.3" x 10.6"
Resolution	1280(H) x 1024(V) dots
Brightness Rating	250 cd/m <sup>2</sup> (Nit)
Contrast Ratio	1000:1
Back Light	CCFT (60 K)
PC Compatibility	Yes
Dot Pitch	0.264(H) x 0.264(V)mm
Colors	16.7M
Number of Pixels	1,310,720
Response Time	5ms (Rising/Falling)
Audio Power / Speakers	8 ohm, 2W, x 2
Viewing Angle (L/R/T/B)	85/85/85/85 degrees
Pixel Configuration	Stripe
Input Signal Level	0.7V P-P (positive) 75 Ohm
Dimensions	559 x 483 x 63.5mm / 22" x 19" x 2.5"
Operating Temp/Humidity	50 ~ 104°F or 10 ~ 40°C
Power Requirements	Regulated 12VDC, 4.1 A, negative ground Part No. DC-1500 required for use in vehicles
Power Consumption	45W (max), 3 W
PC	RGB 15-pin D-sub
Audio	3.5 stereo headphone OUT jack
Power	2.5 mm DC IN jack
Weight	<b>Net</b> 8.8kg / 19.3lbs <b>Gross</b> 11.5kg / 25.2lbs
Installer's Cut Out	19" x 16 5/8"
RoHS Compliant	Yes
GSA	Yes