



LED-1002HDLX

This 9.7" flush mount monitor features the latest screen imaging technology for enhanced clarity and sharpness. Both analog and digital video will benefit by being viewed on this monitor, and it is the best match for displaying higher resolution

Benefits

- LED backlight for better color, longer-life, and lower power
- Wide viewing angle
- Excellent contrast ratio
- Very fast response time
- Image enhancing - 3D Interlace comb filter, DNR, 4H filter
- Durable metal case
- No front controls

Accessories

- DC-1500 Factory approved car cord
- HM-400 Under-cabinet hinge mount
- WM-31 Wall mount bracket (fixed)
- WM-302 Wall mount with swing arm & 4-way adjustable

Related products

- LED-1002HD - Free Standing
- LED-1002HDX - Free standing with no front controls
- LED-1002HDL - Flush mount
- LED-1002HD2 - Dual 9.7 monitors in a rack mount

Installer's Cutout

223 x 221.4mm / 8 7/8" x 8 13/16"

Specifications	
Mount	Flush Mount
HD Compatible	Yes
Anti Glare Coating	Yes
V Chip/Closed Caption	N/A
Selectable Color Temp.	Yes
Case	Metal
IR Remote Control	Yes
Native Aspect Ratio	4:3
Visible Screen Size (WH)	197.6 x 148.8mm / 7.8" x 5.9"
Resolution	1024(H) x 768(V)
Brightness Rating	400 cd/m ² (Nit)
Contrast Ratio	1000:1
Back Light	LED (30K)
PC Compatibility	Yes
Dot Pitch	0.192 (H) x 0.192 (V)mm
Color Depth	262,144
Number of Pixels	786,432
Response Time	2ms/2ms (Rising/Falling)
Audio Power / Speakers	X2 Speakers
Viewing Angle (L/R/T/B)	89/89/89/89 degrees
Pixel Configuration	RGB Vertical Stripe
Input Signal Level	1.0V P-P (positive) 75 Ohm
DSP	3D Interlace comb filter, DNR, 4H filter
Dimensions	10 3/4" x 10 11/16"
Operating Temp/Humidity	32 ~ 104°F or 0 ~ 40°C
Power Requirements	12VDC, 2A, negative ground
Power Consumption	30W (Max)
Component	No
Composite	BNC IN/OUT jacks x 2
PC	15-pin mini D-sub
HDMI	Yes
Audio	RCA L/R IN, PC 3.5mm IN
Power	2.1mm DC IN jack
Weight	4 lbs. net , 6.25lbs. gross
GSA	No