



LED-1906HDT

High-definition, LED-backlit, mid-size monitor that is versatile and effective for any commercial video use.

Benefits

- Displays HD signals (1080i/p and 720p)
- 3D + 3D image processing with digital noise reduction
- Built-in ATSC / Clear QAM Tuner
- Durable ABS Plastic Housing
- Built-in speakers
- Built-in removable deskstand
- 75mm VESA pattern for mounting
- IR remote control

Accessories

- HM-401: Under-cabinet hinge mount
- WM-31: Wall mount bracket (fixed)
- WM-302: Wall mount with swing arm & 4-way adjustable
- WMC-2346: Ceiling mount bracket for 1.5" NPT pipe

Related Products

- LCD-1906HDTL: Flush mount version
- LCD-1906HDTR: Rack mount version



Specifications	
Mount	VESA 75 x 75mm; Removable Deskstand
Screen Panel	18.5" TFT Active Matrix
HD Compatible	Yes
Anti Glare Coating	Yes
Case	Durable ABS Plastic
IR Remote Control	Yes
Native Aspect Ratio	16:9
Visible Screen Size (WH)	16.1" x 9.1" / 409.8 x 230.4mm
Resolution	1366(H) x 768(V)
Brightness Rating	230 cd/m ² (Nit)
Contrast Ratio	1000:1
Back Light	LED (30K)
Dot Pitch	0.30(H) x 0.30(V)mm
Color Depth	16.7M
Number of Pixels	1,049,088
Response Time	5ms (Rising/Falling)
Audio Power / Speakers	8 Ohm, 2 Speakers x 2 Watts
Viewing Angle (L/R/T/B)	85/85/80/80 degrees
3D Comb Filter	Yes
Dimensions	18.5" x 14.25" x 1.4" / 469 x 362 x 36mm
Operating Temp	6 ~ 104°F / -14 ~ 40°C
Power Requirements	100 ~ 240 VAC; 50/60 Hz
Power Consumption	<25 Watts (Max); <= 0.5 Watts (Stand-by)
Component	x1 RCA YPbPr Input
Composite	x2 RCA Inputs; x1 RCA Output
VGA	x1 15-pin mini D-sub Input
HDMI	x3 Inputs
TV (RF)	x1 F (Coax) Input
Audio	x1 RCA L/R Output; x1 3.5mm earphone Output
Weight	Net: 8.8 lbs / 4 kg; Gross: 11 lbs / 5 kg

Specifications subject to change.