

## LED-2361HDMT - Front



## LED-2361HDMT - Back



## LED-2361HDMT

Our NEW digital signage monitor with TV tuner provides a stunning HD picture on a smaller scale for more personal viewing.

### Benefits

- True HD (1080p/i) with no downscaling
- LED backlight – brighter picture using less power
- Widescreen (16:9) native aspect ratio
- Metal case – front even bezel, no front controls; VESA mounting pattern
- ATSC/QAM TV tuner
- IR remote control
- RS-232 control

### Accessories

- HM-400** Under-cabinet hinge mount
- WM-31** Fixed VESA wall mount bracket, 40 lbs. limit
- WM-302** Wall mount with swing arm & 4-way adjustment
- WMC-2342** Ceiling mount bracket (order with WM-31)

### Related Products

LED-2361HD

Specifications	
Mount	Wall: VESA 100mm x 100mm
HD Compatible	Yes
Anti Glare Coating	Yes
Selected Color Temp.	Yes
Case	Metal
Built-in Power Supply	Yes
IR Remote Control	Yes
180° Rotation Display	No
Native Aspect Ratio	16:9
Visible Screen Size (WH)	518 x 295mm / 20.4" x 11.6"
Resolution	1920(H) x 1080 Full HD
Brightness Rating	300 cd/m <sup>2</sup>
Contrast Ratio	1,000:1
Back Light	LED (30k)
PC Compatibility	Yes
Dot Pitch	0.2715(H) x 0.2715(V)mm
Colors	16.7M
Number of Pixels	2,073,600
Response Time	1.5ms/3.5ms (Rising/Falling)
Audio Power / Speakers	1 Speaker 3.5W / 8 Ohm x 2
Viewing Angle (L/R/T/B)	85/85/80/80 degrees
Pixel Configuration	Stripe
Input Signal Level	1.0V P-P (positive) 75 Ohm
Dimensions w/ Deskstand	N/A
Dimensions w/o Deskstand	584 x 356 x 51 mm / 23" x 14" x 2"
Operating Temp/Humidity	32 ~ 122°F / 0 ~ 50°C
Power Requirements	100 ~ 240 VAC, 50/60Hz
Power Consumption	Active < 65 W
Component	RCA Video IN
Composite	1 RCA Video IN
RoHS Compliant	Yes
S-Video	Video IN
PC	D-sub 15pin
HDMI / DVI / RS-232	x2 / No / 3.5mm
Audio	RCA L/R IN/OUT, PC audio IN
Power	A/C Socket
Weight	<b>Net:</b> 6.1 kg / 13.4 lbs <b>Gross:</b> 7.7 kg / 16.95 lbs