



## **LED-2364HD**

This LED-backlit monitor features the latest technology with enhanced picture clarity and sharpness which is ideal for broadcast production and video surveillance applications.

## Benefit

IR Remote Control

LED backlight: brighter picture using less power
Full HD (1080i/p) with no downscaling
Great picture quality with motion adaptive 3D De-interlace noise reduction
RS-232 Control

Mount  HD Compatible  Anti Glare Coating  Case  Durable ABS Plastic  IR Remote Control  Yes  Native Aspect Ratio  Visible Screen Size (WH)  Resolution  Brightness Rating  Contrast Ratio  Back Light  LED  Color Depth  Number of Pixels  Viewing Angle (L/R/T/B)  Digital Signal Processor  Dimensions  Operating Temp  Humidity  Power Requirements  Power Consumption  VESA 100 x 1000 mm  Yes  Auti Opana Plastic  Input  Autio Power / Speakers  Autio Power F / O ~ 40°C  Autio Power Requirements  Autio Power Requirements  Autio Power Consumption  Autio Power / Speakers  Autio Power / Speakers  Autio Power	Specifications	
Anti Glare Coating Case Durable ABS Plastic  IR Remote Control Yes Native Aspect Ratio Visible Screen Size (WH) Resolution Brightness Rating Contrast Ratio 3000:1 Back Light LED Color Depth 16.7 million Number of Pixels 2,073,600 Response Time Audio Power / Speakers Viewing Angle (L/R/T/B) Digital Signal Processor Dimensions Operating Temp Humidity 10% ~ 90% Power Consumption VGA x1 Input Composite RS-232 x1 Input Neight Net: 9.04 lbs / 4.1 kg; Ves Sponse Time Divisible Screen Size (WH) Yes Notice Size (WH) 20.5" x 11.54" / 521.28 x 293.22mm Post 20.6" x 11.54	Mount	VESA 100 x 100mm
Case Durable ABS Plastic  IR Remote Control Yes  Native Aspect Ratio 16:9  Visible Screen Size (WH) 20.5" x 11.54" / 521.28 x 293.22mm  Resolution 1920 x 1080 (Full HD)  Brightness Rating 250 cd/m² (Nit)  Contrast Ratio 3000:1  Back Light LED  Color Depth 16.7 million  Number of Pixels 2,073,600  Response Time 5ms (Rising/Falling)  Audio Power / Speakers 2 Speakers x 2.5 Watts  Viewing Angle (L/R/T/B) 85/85/85/85 degrees  Digital Signal Processor 3D Comb Filter  Dimensions 22.6" x 14" x 1.8" / 573.3 x 355.2 x 46.7mm  Operating Temp 32 ~ 104"F / 0 ~ 40°C  Humidity 10% ~ 90%  Power Requirements 100 ~ 240 VAC, 50/60 Hz; 12VDC / 3.3A; AC adapter included  Power Consumption <35 Watts (Active) / 0.5 Watts (Stand-by)  VGA x1 Input  HDMI x1 Input  Composite x2 BNC Inputs / Outputs  RS-232 x1 Input  Audio x2 Inputs  Power x1 DC12V Input  Weight Net: 9.04 lbs / 4.1 kg;	HD Compatible	Yes
R Remote Control   Yes	Anti Glare Coating	Yes
Native Aspect Ratio  Visible Screen Size (WH)  Resolution  Prightness Rating  Contrast Ratio  Back Light  Color Depth  Number of Pixels  Audio Power / Speakers  Digital Signal Processor  Dimensions  Operating Temp  Humidity  Power Requirements  Power Consumption  VGA  HDMI  Composite  Resolution  16:9  20:5" x 11.54" / 521.28 x 293.22mm  1920 x 1080 (Full HD)  Power (Nit)  Cond (Full HD)  Pour (Nit)  10:00:1  10:00:	Case	Durable ABS Plastic
Visible Screen Size (WH)         20.5" x 11.54" / 521.28 x 293.22mm           Resolution         1920 x 1080 (Full HD)           Brightness Rating         250 cd/m² (Nit)           Contrast Ratio         3000:1           Back Light         LED           Color Depth         16.7 million           Number of Pixels         2,073,600           Response Time         5ms (Rising/Falling)           Audio Power / Speakers         2 Speakers x 2.5 Watts           Viewing Angle (L/R/T/B)         85/85/85/85 degrees           Digital Signal Processor         3D Comb Filter           Dimensions         22.6" x 14" x 1.8" / 573.3 x 355.2 x 46.7mm           Operating Temp         32 ~ 104"F / 0 ~ 40°C           Humidity         10% ~ 90%           Power Requirements         100 ~ 240 VAC, 50/60 Hz; 12VDC / 3.3A; AC adapter included           Power Consumption         <35 Watts (Active) / 0.5 Watts (Stand-by)           VGA         x1 Input           HDMI         x1 Input           Composite         x2 BNC Inputs / Outputs           RS-232         x1 Input           S-Video         x1 Input           Audio         x2 Inputs           Power         x1 DC12V Input           Weight         Net: 9.04 lbs / 4.	IR Remote Control	Yes
Resolution         1920 x 1080 (Full HD)           Brightness Rating         250 cd/m² (Nit)           Contrast Ratio         3000:1           Back Light         LED           Color Depth         16.7 million           Number of Pixels         2,073,600           Response Time         5ms (Rising/Falling)           Audio Power / Speakers         2 Speakers x 2.5 Watts           Viewing Angle (L/R/T/B)         85/85/85/85 degrees           Digital Signal Processor         3D Comb Filter           Dimensions         22.6" x 14" x 1.8" / 573.3 x 355.2 x 46.7mm           Operating Temp         32 ~ 104*F / 0 ~ 40*C           Humidity         10% ~ 90%           Power Requirements         100 ~ 240 VAC, 50/60 Hz; 12VDC / 3.3A; AC adapter included           Power Consumption         <35 Watts (Active) / 0.5 Watts (Stand-by)           VGA         x1 Input           HDMI         x1 Input           Composite         x2 BNC Inputs / Outputs           RS-232         x1 Input           S-Video         x1 Input           Audio         x2 Inputs           Power         x1 DC12V Input           Weight         Net: 9.04 lbs / 4.1 kg;	Native Aspect Ratio	16:9
Brightness Rating 250 cd/m² (Nit)  Contrast Ratio 3000:1  Back Light LED  Color Depth 16.7 million  Number of Pixels 2,073,600  Response Time 5ms (Rising/Falling)  Audio Power / Speakers 2 Speakers x 2.5 Watts  Viewing Angle (L/R/T/B) 85/85/85 degrees  Digital Signal Processor 3D Comb Filter  Dimensions 22.6″ x 14" x 1.8" / 573.3 x 355.2 x 46.7mm  Operating Temp 32 ~ 104°F / 0 ~ 40°C  Humidity 10% ~ 90%  Power Requirements 100 ~ 240 VAC, 50/60 Hz; 12VDC / 3.3A; AC adapter included  Power Consumption <35 Watts (Active) / 0.5 Watts (Stand-by)  VGA x1 Input  HDMI x1 Input  Composite x2 BNC Inputs / Outputs  RS-232 x1 Input  Audio x2 Inputs  Power x1 DC12V Input  Weight Net: 9.04 lbs / 4.1 kg;	Visible Screen Size (WH)	20.5" x 11.54" / 521.28 x 293.22mm
Contrast Ratio 3000:1  Back Light LED  Color Depth 16.7 million  Number of Pixels 2,073,600  Response Time 5ms (Rising/Falling)  Audio Power / Speakers 2 Speakers x 2.5 Watts  Viewing Angle (L/R/T/B) 85/85/85 degrees  Digital Signal Processor 3D Comb Filter  Dimensions 22.6" x 14" x 1.8" / 573.3 x 355.2 x 46.7mm  Operating Temp 32 ~ 104 ° F / 0 ~ 40 ° C  Humidity 10% ~ 90%  Power Requirements 100 ~ 240 VAC, 50/60 Hz; 12VDC / 3.3A; AC adapter included  Power Consumption <35 Watts (Active) / 0.5 Watts (Stand-by)  VGA x1 Input  HDMI x1 Input  Composite x2 BNC Inputs / Outputs  RS-232 x1 Input  S-Video x1 Input  Audio x2 Inputs  Power x1 DC12V Input  Weight Net: 9.04 lbs / 4.1 kg;	Resolution	1920 x 1080 (Full HD)
Back Light  Color Depth  16.7 million  Number of Pixels  2,073,600  Response Time  Sms (Rising/Falling)  Audio Power / Speakers  2 Speakers x 2.5 Watts  Viewing Angle (L/R/T/B)  B5/85/85/85 degrees  Digital Signal Processor  Dimensions  22.6" x 14" x 1.8" / 573.3 x 355.2 x 46.7mm  Operating Temp  32 ~ 104"F / 0 ~ 40°C  Humidity  10% ~ 90%  Power Requirements  100 ~ 240 VAC, 50/60 Hz; 12VDC / 3.3A; AC adapter included  Power Consumption  35 Watts (Active) / 0.5 Watts (Stand-by)  VGA  x1 Input  HDMI  x1 Input  Composite  x2 BNC Inputs / Outputs  RS-232  x1 Input  Audio  x2 Inputs  Power  x1 DC12V Input  Weight  Net: 9.04 lbs / 4.1 kg;	Brightness Rating	250 cd/m <sup>2</sup> (Nit)
Color Depth 16.7 million  Number of Pixels 2,073,600  Response Time 5ms (Rising/Falling)  Audio Power / Speakers 2 Speakers x 2.5 Watts  Viewing Angle (L/R/T/B) 85/85/85/85 degrees  Digital Signal Processor 3D Comb Filter  Dimensions 22.6" x 14" x 1.8" / 573.3 x 355.2 x 46.7mm  Operating Temp 32 ~ 104°F / 0 ~ 40°C  Humidity 10% ~ 90%  Power Requirements 100 ~ 240 VAC, 50/60 Hz; 12VDC / 3.3A; AC adapter included  Power Consumption <35 Watts (Active) / 0.5 Watts (Stand-by)  VGA x1 Input  HDMI x1 Input  Composite x2 BNC Inputs / Outputs  RS-232 x1 Input  S-Video x1 Input  Audio x2 Inputs  Power x1 DC12V Input  Weight Net: 9.04 lbs / 4.1 kg;	Contrast Ratio	3000:1
Number of Pixels         2,073,600           Response Time         5ms (Rising/Falling)           Audio Power / Speakers         2 Speakers x 2.5 Watts           Viewing Angle (L/R/T/B)         85/85/85/85 degrees           Digital Signal Processor         3D Comb Filter           Dimensions         22.6" x 14" x 1.8" / 573.3 x 355.2 x 46.7mm           Operating Temp         32 ~ 104°F / 0 ~ 40°C           Humidity         10% ~ 90%           Power Requirements         100 ~ 240 VAC, 50/60 Hz; 12VDC / 3.3A; AC adapter included           Power Consumption         <35 Watts (Active) / 0.5 Watts (Stand-by)           VGA         x1 Input           HDMI         x1 Input           Composite         x2 BNC Inputs / Outputs           RS-232         x1 Input           S-Video         x1 Input           Audio         x2 Inputs           Power         x1 DC12V Input           Weight         Net: 9.04 lbs / 4.1 kg;	Back Light	LED
Response Time  Audio Power / Speakers  2 Speakers x 2.5 Watts  Viewing Angle (L/R/T/B)  B5/85/85/85 degrees  Joigital Signal Processor  Jomensions  22.6" x 14" x 1.8" / 573.3 x 355.2 x 46.7mm  Operating Temp  32 ~ 104"F / 0 ~ 40"C  Humidity  10% ~ 90%  Power Requirements  100 ~ 240 VAC, 50/60 Hz; 12VDC / 3.3A; AC adapter included  Power Consumption  435 Watts (Active) / 0.5 Watts (Stand-by)  VGA  x1 Input  HDMI  x1 Input  Composite  x2 BNC Inputs / Outputs  RS-232  x1 Input  S-Video  x1 Input  Audio  x2 Inputs  Power  x1 DC12V Input  Weight  Net: 9.04 lbs / 4.1 kg;	Color Depth	16.7 million
Audio Power / Speakers         2 Speakers x 2.5 Watts           Viewing Angle (L/R/T/B)         85/85/85/85 degrees           Digital Signal Processor         3D Comb Filter           Dimensions         22.6" x 14" x 1.8" / 573.3 x 355.2 x 46.7mm           Operating Temp         32 ~ 104°F / 0 ~ 40°C           Humidity         10% ~ 90%           Power Requirements         100 ~ 240 VAC, 50/60 Hz; 12VDC / 3.3A; AC adapter included           Power Consumption         <35 Watts (Active) / 0.5 Watts (Stand-by)           VGA         x1 Input           HDMI         x1 Input           Composite         x2 BNC Inputs / Outputs           RS-232         x1 Input           S-Video         x1 Input           Audio         x2 Inputs           Power         x1 DC12V Input           Weight         Net: 9.04 lbs / 4.1 kg;	Number of Pixels	2,073,600
Viewing Angle (L/R/T/B)         85/85/85/85 degrees           Digital Signal Processor         3D Comb Filter           Dimensions         22.6" x 14" x 1.8" / 573.3 x 355.2 x 46.7mm           Operating Temp         32 ~ 104°F / 0 ~ 40°C           Humidity         10% ~ 90%           Power Requirements         100 ~ 240 VAC, 50/60 Hz; 12VDC / 3.3A; AC adapter included           Power Consumption         <35 Watts (Active) / 0.5 Watts (Stand-by)           VGA         x1 Input           HDMI         x1 Input           Composite         x2 BNC Inputs / Outputs           RS-232         x1 Input           S-Video         x1 Input           Audio         x2 Inputs           Power         x1 DC12V Input           Weight         Net: 9.04 lbs / 4.1 kg;	Response Time	5ms (Rising/Falling)
Digital Signal Processor         3D Comb Filter           Dimensions         22.6" x 14" x 1.8" / 573.3 x 355.2 x 46.7mm           Operating Temp         32 ~ 104°F / 0 ~ 40°C           Humidity         10% ~ 90%           Power Requirements         100 ~ 240 VAC, 50/60 Hz; 12VDC / 3.3A; AC adapter included           Power Consumption         <35 Watts (Active) / 0.5 Watts (Stand-by)           VGA         x1 Input           HDMI         x1 Input           Composite         x2 BNC Inputs / Outputs           RS-232         x1 Input           S-Video         x1 Input           Audio         x2 Inputs           Power         x1 DC12V Input           Weight         Net: 9.04 lbs / 4.1 kg;	Audio Power / Speakers	2 Speakers x 2.5 Watts
Dimensions         22.6" x 14" x 1.8" / 573.3 x 355.2 x 46.7mm           Operating Temp         32 ~ 104°F / 0 ~ 40°C           Humidity         10% ~ 90%           Power Requirements         100 ~ 240 VAC, 50/60 Hz; 12VDC / 3.3A; AC adapter included           Power Consumption         <35 Watts (Active) / 0.5 Watts (Stand-by)           VGA         x1 Input           HDMI         x1 Input           Composite         x2 BNC Inputs / Outputs           RS-232         x1 Input           S-Video         x1 Input           Audio         x2 Inputs           Power         x1 DC12V Input           Weight         Net: 9.04 lbs / 4.1 kg;	Viewing Angle (L/R/T/B)	85/85/85/85 degrees
Operating Temp         32 ~ 104°F / 0 ~ 40°C           Humidity         10% ~ 90%           Power Requirements         100 ~ 240 VAC, 50/60 Hz; 12VDC / 3.3A; AC adapter included           Power Consumption         <35 Watts (Active) / 0.5 Watts (Stand-by)           VGA         x1 Input           HDMI         x1 Input           Composite         x2 BNC Inputs / Outputs           RS-232         x1 Input           S-Video         x1 Input           Audio         x2 Inputs           Power         x1 DC12V Input           Weight         Net: 9.04 lbs / 4.1 kg;	Digital Signal Processor	3D Comb Filter
Humidity 10% ~ 90%  Power Requirements 100 ~ 240 VAC, 50/60 Hz; 12VDC / 3.3A; AC adapter included  Power Consumption <35 Watts (Active) / 0.5 Watts (Stand-by)  VGA x1 Input  HDMI x1 Input  Composite x2 BNC Inputs / Outputs  RS-232 x1 Input  S-Video x1 Input  Audio x2 Inputs  Power x1 DC12V Input  Weight Net: 9.04 lbs / 4.1 kg;	Dimensions	22.6" x 14" x 1.8" / 573.3 x 355.2 x 46.7mm
Power Requirements  100 ~ 240 VAC, 50/60 Hz; 12VDC / 3.3A; AC adapter included  Power Consumption  VGA  x1 Input  HDMI  x1 Input  Composite  x2 BNC Inputs / Outputs  RS-232  x1 Input  S-Video  x1 Input  Audio  x2 Input  Audio  x2 Inputs  Net: 9.04 lbs / 4.1 kg;	Operating Temp	32 ~ 104°F / 0 ~ 40°C
Power Requirements  AC adapter included  Power Consumption	Humidity	10% ~ 90%
VGA         x1 Input           HDMI         x1 Input           Composite         x2 BNC Inputs / Outputs           RS-232         x1 Input           S-Video         x1 Input           Audio         x2 Inputs           Power         x1 DC12V Input           Weight         Net: 9.04 lbs / 4.1 kg;	Power Requirements	
HDMI	Power Consumption	<35 Watts (Active) / 0.5 Watts (Stand-by)
Composite         x2 BNC Inputs / Outputs           RS-232         x1 Input           S-Video         x1 Input           Audio         x2 Inputs           Power         x1 DC12V Input           Weight         Net: 9.04 lbs / 4.1 kg;	VGA	x1 Input
RS-232         x1 Input           S-Video         x1 Input           Audio         x2 Inputs           Power         x1 DC12V Input           Weight         Net: 9.04 lbs / 4.1 kg;	HDMI	x1 Input
S-Video x1 Input Audio x2 Inputs Power x1 DC12V Input Weight Net: 9.04 lbs / 4.1 kg;	Composite	x2 BNC Inputs / Outputs
Audio x2 Inputs  Power x1 DC12V Input  Net: 9.04 lbs / 4.1 kg;	RS-232	x1 Input
Power         x1 DC12V Input           Weight         Net: 9.04 lbs / 4.1 kg;	S-Video	x1 Input
Net: 9.04 lbs / 4.1 kg;	Audio	x2 Inputs
Weight	Power	x1 DC12V Input
, 3	Weight	, 6,

Specifications subject to change.