

LED-430X4-3GSDI - Front



LED-430X4-3GSDI

Functional and beautiful, this new generation model includes four LED-backlit, LCD monitors in a rack mount configuration. Each 4" monitor includes a native 3G-SDI input signal that is SMPTE 424M compliant, handling bit-rates of 2.97Gbit/sec which supports 1080p video up to 60 frames per second. This model is an ideal solution for broadcast studio environments that distribute and monitor VOD 1080p streams.

Benefits

- 3G/HD/SD-SDI Input and Output
- Quick access source buttons
- Wide viewing angle
- Up/Down tilting
- Tally function

Related Products

LED-500X3-3GSDI

LED-430X4-3GSDI - Back



| Specifications | |
|--------------------------|---|
| Model | LED-430X4-3GSDI |
| Mount | Rack: 3 RU |
| HD Compatible | yes |
| Case | Durable metal |
| Native Aspect Ratio | 16:9 |
| Visible Screen Size (WH) | 93 x 55.8mm /3.7" x 2.2" |
| Resolution | 800 x 480 dots |
| Brightness Rating | 200 cd/m² (Nit) |
| Contrast Ratio | 400:1 |
| Back Light | LED (15 K) |
| Dot Pitch | 0.116(H) x 0.116(V) |
| Colors | 16.7M |
| Response Time | 20msec |
| Viewing Angle (L/R/T/B) | 65/65/45/65 |
| Dimensions | 19" x 5.25" x 6.9" (3 RU) |
| Operating Temp/Humidity | 32 ~ 185°F or 0 ~ 85°C, 85% RH max. |
| Power Requirements | 12VDC, 5A |
| Power Consumption | 45W (max) |
| Component | [BNC x 3] x 4 |
| Composite | BNC Video IN x 4 |
| S-Video | mini-DIN x 4 |
| PC | D-sub (15 pin) x 4 |
| HDMI | yes |
| Tally Input | D-sub (9 pin) |
| Audio | No |
| Power | screw in DC jack |
| Weight | Net 5.5 kg / 12.1 lbs, Gross 6.7 kg / 14.75 lbs |