

## Isobar 2-Outlet Surge Protector, Direct Plug-in, 1410 Joules, 3 Diagnostic LEDS, 4-in. Height

MODEL NUMBER: ISOBLOK2-0



### Highlights

- 2 outlets/direct plug-in
- 1410 joule rating
- Diagnostic LEDS
- All-metal housing
- \$10,000 Ultimate Lifetime Insurance (USA, Puerto Rico & Canada only)

### Applications

- Printers, audio/visual devices, appliances, personal computers, point-of-sale terminals, and more.

### Package Includes

- ISOBLOK2-0 Surge Suppressor
- Warranty Information
- Owner's manual

### Description

Tripp Lite's Isobar ISOBLOK2-0 Surge Suppressor is ideal for protecting audio/visual devices and printers. This premium direct plug-in surge suppressor features 2 outlets, diagnostic LED, and 1410 joules of energy absorption. An all-metal housing stands up to the toughest environments. \$10,000 Ultimate Lifetime Insurance (USA and Canada Only).

### Features

- Tripp Lite's ISOBAR is the world's number one selling premium suppressor series with more than 14 million satisfied customers and a safety-tested history of 20+ years.
- 2 outlets with a direct plug-in design
- Surge energy absorption: 1410 joules/48,000 amps
- Diagnostic LEDs indicate "protection present" (green), "grounded" (red) and "line ok" (green)
- EMI/RFI noise filtering
- All-metal housing
- \$10,000 Ultimate Lifetime Insurance (USA and Canada Only) covers connected equipment

## Specifications

| OUTPUT                  |            |
|-------------------------|------------|
| Frequency Compatibility | 50 / 60 Hz |
| Output Receptacles      | (2) 5-15R  |
| Output (Watts)          | 1800       |
| Circuit Breaker (amps)  | 15         |
| USB Charging            | No         |



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
[www.tripplite.com](http://www.tripplite.com)

| INPUT                               |                                                                                              |
|-------------------------------------|----------------------------------------------------------------------------------------------|
| Nominal Input Voltage(s) Supported  | 120V AC                                                                                      |
| Recommended Electrical Service      | 120V (110-125V)                                                                              |
| Input Connection Type               | NEMA 5-15P input plug                                                                        |
| Input Cord Length (ft.)             | 0                                                                                            |
| Input Cord Length (m)               | 0.00                                                                                         |
| Input Cord Length Details           | Direct Plug-In                                                                               |
| Voltage Compatibility (VAC)         | 120                                                                                          |
| USER INTERFACE, ALERTS & CONTROLS   |                                                                                              |
| Diagnostic LEDs                     | PROTECTION PRESENT (green), LINE FAULT (red) and LINE OK (green)                             |
| SURGE / NOISE SUPPRESSION           |                                                                                              |
| AC Suppression Joule Rating         | 1410                                                                                         |
| AC Suppression Response Time        | NM = 0 ns. CM = <1 ns                                                                        |
| Protection Modes                    | Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression           |
| Clamping Voltage (RMS)              | 140                                                                                          |
| AC Suppression Surge Current Rating | 48,000 amps                                                                                  |
| AC Suppression Components Used      | Metal oxide varistors, toroidal balanced chokes and VHF capacitors                           |
| Safe Thermal Fusing                 | Prevents unsafe conditions during extreme extended overvoltages and catastrophic occurrences |
| UL1449 Let Through Rating           | 330V                                                                                         |
| EMI / RFI Filtering                 | 40-80 dB                                                                                     |
| Immunity                            | Conforms to IEE 587 / ANSI C62.41                                                            |
| DATALINE SURGE SUPPRESSION          |                                                                                              |
| Telephone/DSL Protection            | No                                                                                           |
| Cable (Coax) Protection             | No                                                                                           |
| Network (Ethernet) Protection       | No                                                                                           |
| PHYSICAL                            |                                                                                              |
| Unit Dimensions (hwd / in.)         | 4 x 2.5 x 2.5                                                                                |
| Unit Dimensions (hwd / cm)          | 10.2 x 6.4 x 6.4                                                                             |
| Material of Construction            | Metal                                                                                        |
| Housing Color                       | Light Gray                                                                                   |
| Receptacle Color                    | Black                                                                                        |



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
[www.tripplite.com](http://www.tripplite.com)

|                                                            |                                                                                                           |
|------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------|
| Form Factors Supported                                     | Direct plug-in format with retaining bracket supports wall mounting directly to a standard AC wall socket |
| Metal Case                                                 | Yes                                                                                                       |
| <b>SPECIAL FEATURES</b>                                    |                                                                                                           |
| Right-Angle Plug                                           | No                                                                                                        |
| <b>CERTIFICATIONS</b>                                      |                                                                                                           |
| UL1449 3rd Edition (AC Suppression)                        | Tested to UL1449 3rd Edition by ETL                                                                       |
| cUL / CSA (Canada)                                         | Approved for Canada by ETL                                                                                |
| Approvals                                                  | Exceeds IEEE 587 category A&B specifications                                                              |
| <b>WARRANTY</b>                                            |                                                                                                           |
| Product Warranty Period (Worldwide)                        | Lifetime limited warranty                                                                                 |
| Connected Equipment Insurance (U.S., Canada & Puerto Rico) | \$10,000 <a href="#">Ultimate Lifetime Insurance</a>                                                      |

© 2015 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <http://www.tripplite.com/products/product-certification-agencies>