

20-Outlet Vertical Power Strip, 120V, 15A, 15-ft. Cord, 5-15P, 60 in.

MODEL NUMBER: PS6020





Highlights

- 20 outlets
- Convenient and safe covered, on/off switch
- . 15-amp circuit breaker
- 15-ft. cord
- 60" length

Applications

 Ideal for horizontal or vertical raceway style power distribution in office, workbench, industrial, networking and telecom applications

Package Includes

- PS6020
- Mounting hardware
- Instruction manual

Description

Tripp Lite's PS6020 power strip offers 15 amp, 120V multi-outlet AC power distribution in a convenient 60 inch mountable housing. Ideal for horizontal or vertical raceway style power distribution in office, workbench, industrial, networking and telecom applications. Includes 20 NEMA 5-15R output receptacles with 2.795 inch center-to-center spacing, 15 ft AC line cord and lighted power switch with locking transparent cover to prevent accidental shutoff. Sturdy all-metal extruded aluminum housing stands up to demanding network, laboratory or factory environments.

INPUT/OUTPUT: Input: NEMA 5-15P/Output: 20 NEMA 5-15R

ELECTRICAL: 120V AC, 50/60Hz, 15A

FORMAT: 60 in. corded, mountable power strip

Features

- · Sturdy all-metal 60 inch corded strip format with 2.795 inch center-to-center outlet spacing
- Included mounting hardware
- Includes 20 NEMA 5-15R output receptacles
- Ideal for horizontal or vertical raceway style power distribution in office, workbench, industrial, networking and telecom applications
- Lighted power switch with locking transparent cover prevents accidental shutoff
- 15 amp electrical capacity with circuit breaker
- 120V AC, 50/60Hz electrical compatibility

Specifications

ОИТРИТ	
Frequency Compatibility	50 / 60 Hz
Output Receptacles	(20) 5-15R
Output (Watts)	1800





Circuit Breaker (amps)	15	
Outlet Spacing	2.795 in.	
20-Amp Rating	No	
INPUT		
Nominal Input Voltage(s) Supported	120V AC	
Recommended Electrical Service	15A 120V	
Input Connection Type	Nema 5-15P	
Input Plug Features	Black	
Input Cord Length (ft.)	15	
Input Cord Length (m)	4.572	
Input Cord Gauge Type	14/3 SJT	
Voltage Compatibility (VAC)	120	
GFCI Plug	No	
USER INTERFACE, ALERTS & CON	TROLS	
Switches	Lighted 2 position switch controls power to all outlets	
Locking Switch Cover	Transparent on/off switch cover prevents accidental turn-off	
PHYSICAL		
Unit Dimensions (hwd / in.)	60 x 1.5 x 1.5	
Unit Dimensions (hwd / cm)	152.4 x 3.8 x 3.8	
Unit Weight (lbs.)	5.0	
Unit Weight (kg)	2.27	
Material of Construction	Aluminum	
Included Mounting Accessories	Includes mounting clips	
Receptacle Color	Black	
Color (AC Line Cord)	Black	
Form Factors Supported	Supports horizontal or vertical raceway style power distribution in office, workbench, industrial, networking and telecom applications	
Outlets Measurement (Center to Center)	69mm	
CERTIFICATIONS		
UL1363 (Power Tap)	UL1363	
cUL / CSA (Canada)	cUL	



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

WARRANTY	
Product Warranty Period (Worldwide)	Lifetime limited warranty

© 2015 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: http://www.tripplite.com/products/product-certification-agencies