

Protect It! 7-Outlet Surge Protector, 7-ft. Cord, 2160 Joules, White Housing

MODEL NUMBER: SUPER7



Highlights

- 7 outlets/7 ft. cord
- 2160 joule rating
- \$75,000 Ultimate Lifetime Insurance (U.S., Canada, and Puerto Rico only)

Applications

Personal computers,
CAD/CAM/CAE workstations,
network nodes, fileservers,
point-of-sale terminals,
audio/visual devices, and more.

Package Includes

- Super 7 Surge Suppressor
- Instruction manual with warranty information

Description

The SUPER7 Surge Suppressor from Tripp Lite has 7 outlets, a 7-ft. cord with a space-saving right-angle plug, and diagnostic LEDs. The unit has a surge suppression rating of 2160 joules to handle the strongest surges. \$75,000 Ultimate Lifetime Insurance (U.S., Canada, and Puerto Rico only).

Features

- 7 outlets
- 7-ft. cord with space-saving right-angle plug
- Surge suppression rating: 2160 joules
- . EMI/RFI noise filtering
- Can accommodate up to 3 transformers without blocking remaining outlets
- \$75,000 Ultimate Lifetime Insurance (U.S., Canada, and Puerto Rico only) covers connected equipment
- Diagnostic LEDs indicate protection present & ground present
- . Keyhole supports for wall mounting

Specifications

| ОИТРИТ | |
|---------------------------|--|
| Frequency Compatibility | 50 / 60 Hz |
| Output Receptacles | (7) 5-15R |
| Output (Watts) | 1800 |
| Circuit Breaker (amps) | 15 |
| Transformer Accommodation | Supports 3 large transformer plug accessories without covering remaining outlets, accepts up to 5 transformers total |
| Outlet Orientation | Single row of 5, plus 2 side mounted outlets |



| USB Charging | No | |
|------------------------------------|---|--|
| INPUT | | |
| Nominal Input Voltage(s) Supported | 120V AC | |
| Recommended Electrical Service | 120V (110-125V) | |
| Input Connection Type | NEMA 5-15P | |
| Input Cord Length (ft.) | 7 | |
| Input Cord Length (m) | 2.1 | |
| Input Cord Gauge Type | 14 gauge, SJT | |
| Voltage Compatibility (VAC) | 120 | |
| Maximum Surge Amps | 144000 | |
| USER INTERFACE, ALERTS & CONTROLS | | |
| Switches | Two position on/off power switch | |
| Diagnostic LEDs | Built-in LEDs confirm suppressor "protection present" (green) and "grounded" (red) status | |
| SURGE / NOISE SUPPRESSION | | |
| AC Suppression Joule Rating | 2160 | |
| AC Suppression Response Time | < 1 ns | |
| Protection Modes | Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression | |
| Clamping Voltage (RMS) | 150 | |
| UL1449 Let Through Rating | 330 L-G, 400 L-N, 400 N-G | |
| EMI / RFI Filtering | Up to 20 dB | |
| DATALINE SURGE SUPPRESSION | | |
| Telephone/DSL Protection | No | |
| Cable (Coax) Protection | No | |
| Network (Ethernet) Protection | No | |
| PHYSICAL | | |
| Shipping Dimensions (hwd / in.) | 12.40 x 5.90 x 1.77 | |
| Shipping Dimensions (hwd / cm) | 31.50 x 14.99 x 4.50 | |
| Shipping Weight (lbs.) | 1.56 | |
| Shipping Weight (kg) | 0.71 | |
| Unit Dimensions (hwd / in.) | 1.54 x 2.72 x 10.30 | |
| Unit Dimensions (hwd / cm) | 3.91 x 6.91 x 26.16 | |





| 1.39 | | |
|---|--|--|
| 0.63 | | |
| Plastic | | |
| Keyhole mounting tabs enable wall mounting | | |
| Light gray | | |
| Light Gray | | |
| Light Gray | | |
| Between Standard Outlets = 29mm; Between Transformer Outlets = 48mm | | |
| Distance Between Slots = 78mm; Distance Between Slot Height = 24mm | | |
| No | | |
| SPECIAL FEATURES | | |
| Yes | | |
| CERTIFICATIONS | | |
| UL1449 3RD EDITION | | |
| UL1363 | | |
| cUL | | |
| Exceeds IEEE 587 category A&B specifications | | |
| WARRANTY | | |
| Lifetime limited warranty | | |
| \$75,000 Ultimate Lifetime Insurance | | |
| | | |

© 2015 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: http://www.tripplite.com/products/product-certification-agencies