



Protect It! Surge Protector with 6 Outlets (2-fixed, 4-rotatable), 6-ft. Cord, 1440 Joules, Tel/Modem/Coax Protection

MODEL NUMBER: TLP606RNET











Description

Tripp Lite's TLP606RNET Surge Suppressor provides high-performance protection--1440 joules--stopping damaging surges and filtering disruptive line noise so components perform at their peak! 6 outlets - 4 that rotate, 2 that are standard, 1-line coaxial protection - that also rotates and 1-line tel/modem for maximum protection. \$150,000 Ultimate Lifetime Insurance (U.S., Canada, and Puerto Rico only). Includes two diagnostic LEDs, 6 ft. gold coaxial cable, 6ft network cable and 6 ft. phone cord.

Highlights

- 6 outlets 4 rotate, 2 standard
- 6 ft cord
- 1440 joules
- 1 line tel/modem and 1-line gold coax (2.2GHz bandwidth) protection
- \$150,000 Ultimate Lifetime Insurance (U.S., Canada, and Puerto Rico only)

Applications

 Perfect for small home/business theater installations: high-definition TVs, satellite and A/V receivers, DVD/CD players and more

Package Includes

- TLP606RNET Surge Suppressor
- Instruction manual with warranty information
- 6 ft. gold coaxial cable
- 6 ft. phone cord
- 6 ft network cord

Features

- 6 outlets 4 rotate, 2 standard, allow for easier plug connection and removal
- 1440 joules surge suppression rating with EMI/RFI line noise filtering help components perform at their peak (sharper, crisper video; deeper, fuller audio and longer component life spans)
- 6ft cord
- 1 set of surge-protected gold coaxial connectors (with included 6 ft. coaxial cable) safeguard components on cable, satellite or antenna line (2.2GHz bandwidth)
- 1 set of surge-protected tel/modern.ethernet connectors (with included 6 ft. phone cord and 6ft Network cable)
- 2 diagnostic LEDs alert user to protection and grounding status
- High-impact plastic housing (black) stands up to the most demanding environments
- \$150,000 Ultimate Lifetime Insurance (U.S., Canada, and Puerto Rico only)

Specifications

ОUТРUТ	
Frequency Compatibility	60 Hz





	[
Output Receptacles	(6) 5-15R		
Circuit Breaker (amps)	15		
Outlet Orientation	Rotatable		
USB Charging	No		
INPUT	PUT		
Nominal Input Voltage(s) Supported	120V AC		
Recommended Electrical Service	120V (110-125V)		
Input Connection Type	NEMA 5-15P RIGHT ANGLE		
Input Cord Length (ft.)	6		
Input Cord Length (m)	1.83		
Voltage Compatibility (VAC)	120		
USER INTERFACE, ALERTS & CON	TROLS		
Diagnostic LEDs	Built-in LEDs confirm suppressor "protected" (green) and "grounded" (red) status		
SURGE / NOISE SUPPRESSION			
AC Suppression Joule Rating	1440		
AC Suppression Response Time	< 1 ns		
Protection Modes	Includes full normal mode (H-N) and common mode (N-G/H-G) line surge suppression		
Clamping Voltage (RMS)	300,500,500		
UL1449 Let Through Rating	400, 500, 500		
EMI / RFI Filtering	150KHZ TO 100MHZ		
DATALINE SURGE SUPPRESSION			
Telephone/DSL Protection	Yes		
Telephone/DSL Protection Details	1 line		
Cable (Coax) Protection	Yes		
Cable (Coax) Protection Details	1 line		
Network (Ethernet) Protection	Yes		
PHYSICAL			
Shipping Dimensions (hwd / in.)	12.60 x 6.10 x 2.36		
Shipping Dimensions (hwd / cm)	32 x 15.49 x 5.99		
Shipping Weight (lbs.)	1.54		
Shipping Weight (kg)	0.70		





2.2 x 5.91 x 4.72		
5.6 x 15 x 12		
2.22		
1.00		
Plastic		
Black		
No		
SPECIAL FEATURES		
No		
CERTIFICATIONS		
UL1449 3rd Edition		
cUL		
RoHS		
WARRANTY		
Lifetime limited warranty		
\$150,000 Ultimate Lifetime Insurance		

© 2015 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: http://www.tripplite.com/products/product-certification-agencies