

Protect It! 6-Outlet Surge Protector, 4-ft. Cord, 540 Joules - Accommodates 2 Transformers

MODEL NUMBER: TLP64











Highlights

- . 6 outlets / 4 ft cord
- 540 joule rating
- \$20,000 Ultimate Lifetime Insurance (U.S., Canada, and Puerto Rico only)

Applications

Personal computers, CAD/CAM/CAE work stations, fileservers, point-of-sale terminals and more.

Package Includes

- TLP64
- Instruction manual with warranty information

Description

Tripp Lite's TLP64 offers economical AC surge suppression for protection of workstations, desktop PCs, point-of-sale terminals and other sensitive electronics. Built-in AC surge suppression shields connected equipment from damage and performance problems due to transient surges. TLP64 offers 6 total outlets, 4 foot cord and diagnostic LEDs to warn of suppressor damage. AC suppression rated at 540 joules shields equipment from surges and line noise. Attractive gray suppressor housing with keyhole mounting tabs offer convenient protection of desktop computer equipment and accessories. \$20,000 Ultimate Lifetime Insurance (U.S., Canada, and Puerto Rico only).

Features

- 6 outlets with integrated child safety covers
- 4ft cord
- Surge suppression rating: 540 joules
- EMI/RFI noise filtering
- Can accommodate up to 2 transformers without blocking remaining outlets
- Diagnostic LEDs indicate protection present and ground present
- Keyhole supports for wall mounting
- · Lighted power switch
- \$20,000 Ultimate Lifetime Insurance (U.S., Canada, and Puerto Rico only)

Specifications

ОИТРИТ	
Frequency Compatibility	60 Hz
Output Receptacles	(6) 5-15R
Output (Watts)	1800





Circuit Breaker (amps)	15	
Overload Protection	15A resettable illuminated combo switch / circuit breaker	
Transformer Accommodation	Supports 2 large transformer plug accessory without covering remaining outlets, accepts up to 4 transformers total	
Outlet Safety Covers	6	
Outlet Orientation	Block style 2 rows of 3 outlets	
USB Charging	No	
INPUT		
Nominal Input Voltage(s) Supported	120V AC	
Recommended Electrical Service	120V (110-125V)	
Input Connection Type	NEMA 5-15P	
Input Cord Length (ft.)	4	
Input Cord Length (m)	1.22	
Input Cord Gauge Type	14 gauge, SJT	
Voltage Compatibility (VAC)	120	
Maximum Surge Amps	36000	
USER INTERFACE, ALERTS & CON	TROLS	
Switches	Combination AC circuit breaker and 2 position red illuminated on/off power switch	
Diagnostic LEDs	Built-in LED confirms suppressor "protection present" (green) status	
SURGE / NOISE SUPPRESSION		
AC Suppression Joule Rating	540	
AC Suppression Response Time	< 1 ns	
Protection Modes	Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression	
Clamping Voltage (RMS)	150	
UL1449 Let Through Rating	400v	
EMI / RFI Filtering	Up to 40 dB	
DATALINE SURGE SUPPRESSION		
Telephone/DSL Protection	No	
Cable (Coax) Protection	No	
Network (Ethernet) Protection	No	
PHYSICAL		
Shipping Dimensions (hwd / in.)	11.02 x 7.08 x 1.77	



27.99 x 17.98 x 4.50	
1.65	
0.75	
1.50 x 4.23 x 8.29	
3.81 x 10.74 x 21.06	
1.10	
0.50	
Plastic	
Keyhole mounting tabs enable wall mounting	
Light Gray	
Light Gray	
Light Gray	
Distance between standard outlets = 28.5mm; Distance between standard outlet and transformer outlet = 48.5mm	
119mm	
No	
No	
UL1449 3rd Edition	
UL1363	
cUL	
Exceeds IEEE 587 category A&B specifications	
WARRANTY	
Lifetime limited warranty	
\$20,000 Ultimate Lifetime Insurance	

© 2015 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: http://www.tripplite.com/products/product-certification-agencies