www.tripplite.com



Eco-Surge 6-Outlet Surge Protector, 6-ft. cord, 2100 Joules, Remote-Controlled

MODEL NUMBER: TLP66RCG







Highlights

- Keychain remote control turns GREEN energy saving outlets on/off
- 6 outlet/6-ft cord
- 2100 joules
- \$100,000 Ultimate Lifetime Insurance (U.S., Canada, and Puerto Rico only)

Applications

Ideal for any desktop, network or home computing application requiring AC protection

Package Includes

- TLP66RCG ECO-SURGE Energy-Saving Surge Suppressor
- Owners Manual

Description

Tripp Lite's TLP66RCG offers reliable, GREEN surge technology that protects your computer and peripherals, the environment and your wallet. Energy-saving outlet configuration reduces energy waste (phantom loads) by

cutting AC power to unused peripherals. Convenient, one-touch remote control turns green energy-saving outlets on and off. TLP66RCG has 6 total outlets, 6 foot cord and diagnostic LEDs to warn of wiring problems and suppressor damage. Network-grade AC suppression rated at 2100 joules shields equipment from surges and line noise. Attractive cool gray suppressor housing with keyhole mounting tabs and up to 4 transformer plug outlets offers convenient protection of desktop computer equipment and accessories. \$100,000 Ultimate Lifetime Insurance (U.S., Canada, and Puerto Rico only).

Features

- Energy-saving outlet configuration reduces energy waste (phantom loads) by cutting AC power to unused peripherals
- . 433 MHz key chain remote turns GREEN outlets on/off through walls, doors and furniture from up to 75 ft. away
- 6 total AC outlets with room for 4 transformer plugs
- 4 "Remote/Power Save" GREEN outlets cut AC power to idle components when turned off via remote control perfect for intermittent use equipment like DVD players, gaming consoles, speaker systems, monitors, printers, lighting etc.
- Two "Switched/Always-On" outlets provide continuous power for devices such as DVRs (TiVo), cable and satellite boxes, modems, routers, external hard
 drives, cordless phones and fax machines
- 2100 joules of AC surge suppression shields equipment from the strongest surges and line noise
- Lighted power switch with integrated 15 amp circuit breaker offers power control and overload protection
- . Diagnostic LEDs confirm outlet grounding and surge suppression status
- · Attractive gray suppressor housing with keyhole mounting tabs allow versatile placement options
- \$100,000 Ultimate Lifetime Insurance (U.S., Canada, and Puerto Rico only)

Specifications

OUTPUT





	I	
Output Watt Capacity (Watts)	1800	
Frequency Compatibility	60 Hz	
Output Receptacles	(6) 5-15R	
Circuit Breaker (amps)	15	
Transformer Accommodation	up to 4	
USB Charging	No	
INPUT		
Nominal Input Voltage(s) Supported	120V AC	
Recommended Electrical Service	120V (110-125V)	
Input Connection Type	NEMA 5-15P	
Input Plug Features	Straight plug	
Input Cord Length (ft.)	6	
Input Cord Length (m)	1.83	
Input Cord Gauge Type	14 gauge, SJT	
Voltage Compatibility (VAC)	120	
Maximum Surge Amps	39000	
USER INTERFACE, ALERTS & CONTROLS		
Switches	Combination AC circuit breaker and 2 position red illuminated on/off power switch	
Diagnostic LEDs	Built-in LEDs confirm suppressor "protection present" (green) and "grounded" (red) status and "receiver" (red)	
SURGE / NOISE SUPPRESSION		
AC Suppression Joule Rating	2100	
AC Suppression Response Time	< 1 ns	
Protection Modes	Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression	
UL1449 Let Through Rating	400, 400, 400	
EMI / RFI Filtering	Up to 20db	
DATALINE SURGE SUPPRESSION		
Telephone/DSL Protection	No	
Cable (Coax) Protection	No	
Network (Ethernet) Protection	No	
PHYSICAL		
Shipping Dimensions (hwd / in.)	13.19 x 6.30 x 1.89	





Shipping Dimensions (hwd / cm)	33.50 x 16.00 x 4.80
Shipping Weight (lbs.)	1.73
Shipping Weight (kg)	0.78
Unit Dimensions (hwd / in.)	1.67 x 4.41 x 9.25
Unit Dimensions (hwd / cm)	4.24 x 11.20 x 23.50
Unit Weight (lbs.)	1.45
Unit Weight (kg)	0.66
Material of Construction	Plastic
Integrated Keyhole Mounting Tabs	Keyhole mounting tabs enable wall mounting
Color (AC Line Cord)	Gray
Outlets Measurement (Center to Center)	Distance between "Remoted" outlets = 28.5mm; Distance between "Remoted" and "Switched" outlets = 50mm
Metal Case	No
SPECIAL FEATURES	
Green Energy-Saving Features	Power saving auto-shutoff ECO outlets
Right-Angle Plug	No
CERTIFICATIONS	
UL1449 3rd Edition (AC Suppression)	UL1449 3rd Edition
UL1363 (Power Tap)	UL1363
cUL / CSA (Canada)	cUL
WARRANTY	
Product Warranty Period (Worldwide)	Lifetime limited warranty
Connected Equipment Insurance (U.S., Canada & Puerto Rico)	\$100,000 Ultimate Lifetime Insurance

© 2015 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: http://www.tripplite.com/products/product-certification-agencies