

Tripp Lite 1111 W. 35th Street Chicago, IL 60609 USA Telephone: 773.869.1234 www.tripplite.com

USB 2.0 Hi-Speed Active Extension Cable (A M/F), 16-ft.

MODEL NUMBER: U026-016





Description

Tripp Lite's 16-ft. USB 2.0 Extension Cable is a bus powered extension cable that can be used to increase the length of a device cable without the worry of signal loss and potential performance problems. USB limits a cable's length to 16ft. Any length above 16 feet requires the use of an active cable such as this one. This cable has a signal booster built in. The overall cable length can be extended up to 80ft. by daisy-chaining up to 5 of these active cables. The U026-016 provides up to 150mA of power to the connected device. If your device requires more than 150mA of power, it will either need to have its own power supply or need to be plugged into a powered USB 2.0 hub (such as U222-004-R) that is connected to the U026-016. Use a standard 6' 10' or 15' USB cable to reach the desired distance.

Features

- Extend a USB 2.0 signal passed the 16 ft. (5 m.) distance limitation
- Works together with standard USB 2.0 cables
- Bus powered signal booster
- Daisychain up to 5 cables to extend the signal up to 80 ft. passed the 16 ft. (5 m.) distance limitation
- The U026-016 provides up to 150mA of power to the connected device. If your device requires more than 150mA of power, it will either need to have its own power supply; or, to be plugged into a powered USB 2.0 hub (such as U222-004-R) that is connected to the U026-016.

Specifications

overview Cable Type USB output

Highlights

- Premium double-shielded cables with tinned copper braid and aluminum mylar foil feature twisted 28/20 AWG data lines
- Gold plated contacts provide superior conductivity for low and high speed devices (1.5 to 480 Mbps.)
- Active extension cable regenerates USB signal for extra-long distances: daisy-chain up to 80-ft. in most applications

System Requirements

- A USB 2.0 port and USB 2.0 device are required to achieve USB 2.0 speeds. A USB 1.1 port and/or device can be used, but you will not be able to achieve USB 2.0 speeds.
- The U026-016 provides up to 150mA of power to the connected device. If your device requires more than 150mA of power, it will either need to have its own power supply; or, to be plugged into a powered USB 2.0 hub (such as U222-004-R) that is connected to the U026-016.

Package Includes

 16-ft. USB 2.0 Extension Cable (USB A M/F)



USB Charging No INPUT Cable Length (ft.) 16 Cable Length (m) 4.88 PHYSICAL Color Blace	38
Cable Length (ft.) 16 Cable Length (m) 4.88 PHYSICAL 16	38
Cable Length (ft.) 16 Cable Length (m) 4.88 PHYSICAL 16	38
Cable Length (m) 4.88 PHYSICAL	38
PHYSICAL	
	ack
Color Blac	ack
ENVIRONMENTAL	
Storage Temperature Range -20) to 80 C (-4 to 176 F)
Operating Temperature -20	0 to 80 C (-4 to 176 F)
CONNECTIONS	
Connector A USE	SB A (MALE)
Connector B USE	SB A (FEMALE)
SPECIAL FEATURES	
Chromebook Compatible Yes	s
CERTIFICATIONS	
Certifications RoH	HS-Compliant
WARRANTY	
Product Warranty Period (Worldwide) 1-ye	/ear limited warranty

© 2015 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: http://www.tripplite.com/products/product-certification-agencies