



VZ-TK75A Aluminum Video Tripod w/ Fluid Head

Features:

- Dual-stage legs with mid-level spreader and fluid pan/tilt head
- 75mm bowl mount allows quick leveling without adjusting legs
- Can be attached to the VZ-D50 Dolly for tracking shots (*Sold Separately*).
- For use with cameras 4-10 lbs.
- Switchable rubber/spiked feet
- Includes 1 telescoping handle (second handle may be purchased separately)

***** The handle for the fluid head and the camera mounting screws (1/4"-20 and 3/8"-16) are packed in the side pocket of the carrying bag. *****

The two-stage locking legs allow for a wide range of adjustment from low to high. Make sure when packing the tripod that the legs are locked together using the retractable lanyard clip to prevent damage. To adjust leg length, simply twist the locking knobs. Make sure each knob is secured completely to prevent the leg sections from shifting under the weight of the camera.

The spreader located at the center of the tripod is not adjustable. Please do not try to remove it, as doing so may cause irreparable damage. Switchable rubber/spiked feet allow the tripod to grip many different surfaces – simply thread the rubber feet in or out to expose or hide the spikes.

Attach the handle to the fluid head and choose the appropriate camera mounting screw. To insert the camera mounting screw, you'll have to remove the quick-release plate from the fluid head. On the right hand side is the locking lever – loosen this lever. The plate will now slide, but you'll have to twist the safety catch on the other side to slide the plate out. Insert the screw and mount the plate to your camera, then reinsert the plate into the head, making sure to fully tighten the locking lever – **failure to tighten the locking lever may result in damage to your camera.**



The fluid head will allow smooth pans and tilts with adjustable drag and lock. To lock the pan, all you need to do is tighten the screw at the base of the head. Tilt allows more control, with both a locking mechanism on the left side and a drag adjustment on the right side, for custom adjustments based on the needs of the operator.

The 75mm bowl mount system allows you to level the tripod head without having to precisely adjust the length of each tripod leg. This is advantageous because it's quicker and enables you to change tripod positions over uneven ground without having to constantly adjust the legs. To level the head, loosen the knob on the underside and tilt the head until the bubble level is centered. **To ensure stability**, level the tripod by adjusting the legs **first**, then use the head leveling system for fine adjustments. In the event that you wish to remove the fluid head, simply unscrew the knob located on the underside of the head and extract the head from the tripod bowl.



The VZ-TK75A tripod is covered by a one-year warranty (parts/labor). Please retain your receipt for warranty verification. All returns and repairs must be accompanied by a Return Merchandise Authorization number (RMA #)

Warnings: Do not put more than the recommended weight onto the tripod as you may void your warranty.