Technical Data Sheet Plenum Communication Cables

WEST PENN WIRE



2833 West Chestnut Street Washington, PA 15301 Toll Free: (800) 245-4964 Fax: (724) 222-6420 www.westpenn-wpw.com

253244B **PART NUMBER:**

DESCRIPTION: 18/4 Stranded bare copper conductors, shielded with an overall jacket.

NEC RATING: CMP, NEC Article 800

APPROVALS: (UL) C(UL) Listed or c(ETL)us Listed

Indoor within ducts, plenums, and other spaces used for environmental air for (Intercom Systems, APPLICATION:

Security Systems, Sound, Audio, Background Music)

Construction Parameters:

Conductor 18 AWG Bare Copper

Stranding 7x26

Insulation Material Flex Plenum PVC 0.008" Nom. Insulation Thickness

Number of Conductors

Shield 100% Aluminum Polyester Foil Stranded Tinned Copper Drain Jacket Material Flex Plenum PVC

0.015" Nom. Jacket Thickness 0.182" Nom. Overall Cable Diameter Approximate Cable Weight 36 Lbs/1M' Nom. NFPA 262 Flame Test

Electrical & Environmental Properties:

Temperature Rating -10°C To +60°C Operating Voltage 300 V RMS Max.Capacitance Between Conductors @ 1 KHz 68 pf/ft Nom. Capacitance Between Conductors to Shield @ 1 KHz 122 pf/ft Nom. DC Resistance per Conductor @ 20deg C 6.2 Ohms/1M' Nom. **Insulation Colors** Black, Red, White, Green

Jacket Color **RoHS Compliant**

Mechanical Properties:

Max. Recommended Pull Tension Min. Bend Radius (Install)

Specification Issue Date: 7/06

Flame Rating

This document is the property of West Penn Wire. The information contained herein is considered Proprietary and not to be reproduced by any means Without written consent of West Penn Wire

99 lbs 1.87"

Gray

Yes



Standard Lengths are 1000ft. The Jacket is sequentially footmarked. The information presented here is, to the best of our knowledge, is true and accurate. However, since conditions of use are beyond our control, all recommendations or suggestions are presented without guarantee or responsibility on our part. We disclaim all liability in connection with the use of information contained herein or otherwise.