Technical Data Sheet RG6/U Type CATV Coaxial Cable Plenum WEST PENN WIRE





25Q841 **PART NUMBER:**

DESCRIPTION: RG6/U - 1 Conductor 18 AWG Solid, Quad-Shield and an overall Plenum PVC Jacket.

NEC RATING: CATVP/ CMP

APPROVALS: (UL) C(UL) Listed or c(ETL)us Listed

APPLICATION: Indoor for Plenum:- CATV/MATV

Construction Parameters:

Conductor 18 AWG Bare Copper

Stranding Solid Insulation Material Foam FEP Insulation Thickness .170" Nom.

Number of Conductors 1 Center Conductor

Shield Quad-Shield- 100% Al foil + 65% Al. Braid +

100% Al. Foil + 55% Al. Braid

3000

15.42

Jacket Material Flexible Plenum PVC Overall Cable Diameter 0.273" Nom. 36 Lbs/1M' Nom. Approximate Cable Weight Flame Rating **NFPA 262**

Electrical & Environmental Properties:		Mhz	db/100ft
Temperature Rating	-20deg C to 60deg C	5	.5
Max.Capacitance Between Conductors @ 1 KHz	16.2 pf/ft Nom.	55	1.6
Velocity of Propagation	82% Nom.	100	2.0
Impedance	75 ohms Nom.	270	2.9
DC Resistance per Conductor @ 20deg C	6.5 Ohms/1M' Nom.	400	4.5
Jacket Color Polls Compliant	Ivory Yes	550	4.9
RoHS Compliant	ies	750	6.6
Mechanical Properties:		1000	8.0
<u> •</u>	105 H	2000	12.3
Max. Recommended Pull Tension	125 lbs.	2250	13.36
Min. Bend Radius (Install)	2.7"	2000	15.40

Connectors and Accessories

F Crimp: CN-56ALM CN-DB6PL2 F Compression:

Specification Issue Date: 7/06

This document is the property of West Penn Wire. The information contained herein is considered Proprietary and not to be reproduced by any means Without written consent of West Penn Wire

Standard Lengths are 1000ft. The Jacket is sequentially footmarked. The information presented here is, to the best of our knowledge, is true and accurate. However, since conditions of use are beyond our control, all recommendations or suggestions are presented without guarantee or responsibility on our part. We disclaim all liability in connection with the use of information contained herein or otherwise.