

Technical Data Sheet Communication Cables



2833 West Chestnut Street
Washington, PA 15301
Toll Free: (800) 245-4964
Fax: (724) 222-6420
www.westpenn-wpw.com

PART NUMBER:	3245
DESCRIPTION:	16/4 Stranded bare copper conductors, shielded with an overall jacket.
NEC RATING:	CMR, NEC Article 800
APPROVALS:	(UL) C(UL) Listed or c(ETL)us Listed
APPLICATION:	Indoor for: Intercom, Security, Sound, Audio, Background Music, and Power Limited Control Circuits.

Construction Parameters:

Conductor	16 AWG Bare Copper
Stranding	19x29
Insulation Material	Polypropylene
Insulation Thickness	0.008" Nom.
Number of Conductors	4
Shield	100% Aluminum Polyester Foil
Drain	Stranded Tinned Copper
Jacket Material	PVC
Jacket Thickness	0.017" Nom.
Overall Cable Diameter	0.225" Nom.
Approximate Cable Weight	50.5 Lbs/1M' Nom.
Flame Rating	UL 1666 Riser Flame Test

Electrical & Environmental Properties:

Temperature Rating	-20°C To +60°C
Operating Voltage	300 V RMS
Max.Capacitance Between Conductors @ 1 KHz	45 pf/ft Nom.
Capacitance Between Conductors to Shield @ 1 KHz	89 pf/ft Nom.
DC Resistance per Conductor @ 20deg C	4.2 Ohms/1M' Nom.
Insulation Colors	Black, Red ,White ,Green
Jacket Color	Gray
RoHS Compliant	Yes

Mechanical Properties:

Max. Recommended Pull Tension	146.3 lbs.
Min. Bend Radius (Install)	2.2"

Specification Issue Date: 7/14

This document is the property of West Penn Wire.
The information contained herein is considered
Proprietary and not to be reproduced by any means
Without written consent of West Penn Wire

Standard Lengths are 1000ft.
The Jacket is sequentially footmarked.
The information presented here is, to the best of our
knowledge, is true and accurate. However, since
conditions of use are beyond our control, all
recommendations or suggestions are presented
without guarantee or responsibility on our part. We
disclaim all liability in connection with the use of
information contained herein or otherwise.