

4246

4 Pair 23AWG UTP Category 6 CMR

10/100/1000 BaseT Ethernet, IP CCTV, Digital Integration, HDBaseT

Construction & Dimensions


CONDUCTOR PARAMETERS	
Number Of Pairs	4
AWG Size	23
Conductor Stranding	Solid
Conductor Type	Bare Copper
Nominal DCR	24 Ohm/1000ft
INSULATION PARAMETERS	
Insulation Type	Polyolefin
Insulation Color Code	1.Blue,WH-Blue 2.Orange,WH-Orange 3.Green,WH-Green 4.Brown, WH-Brown
SHIELDING PARAMETERS	
Shield Type	Unshielded Twisted Pair (UTP)
ELECTRICAL CHARACTERISTICS	
Nominal Impedance	100 Ohm
Nominal Capacitance Between Conductors	15 pF/ft

Overall Construction

OVERALL CONSTRUCTION PARAMETERS	
Total Number of Conductors	8
Jacket Type	PVC
Nominal Cable O.D.	0.22 in
Plenum	No
NEC UL Rating	CMR
RoHS Compliant	Yes
ANSI/TIA Category	Category 6 TIA/EIA 568C.2
TIA Test	ANSI/TIA-568-C.2
Pull Tension	40 lbs
Bend Radius	1.1 in
Cable Weight	29 lbs

Overall Electrical & Optical Characteristics

OVERALL ELECTRICAL/OPTICAL CHARACTERISTICS	
Nominal Velocity of Propagation (VP)	72 %
Delay Skew	45 ns/100m
UL Flammability	UL1666 Vertical Shaft
CSA Flammability	FT4
Operating Range	-0 to 75 Deg C
UL Voltage Rating	300



4246

Electrical Performance

Frequency (Mhz)	Max. Insertion Loss	Min. NEXT	Min. PSNEXT	Min. PSACR	Min. ACR	Min. PSACRF (PSELF-EXT)	Min. ACRF (ELF-EXT)	Min. RL (Return Loss)	Max/Min Input Imp. Unfit	Max/Min Fitted Imp.
1 MHz	2 db/100m	75.3 dB	73.3 dB	71.3 dB	73.3 dB	67.8 dB	70.8 dB	20 dB	100 ± 15 Ohm	100 ± 15 Ohm
4 MHz	3.7 db/100m	66.3 dB	64.3 dB	60.6 dB	62.6 dB	55.8 dB	58.8 dB	23 dB	100 ± 15 Ohm	100 ± 15 Ohm
8 MHz	5.2 db/100m	63.3 dB	61.3 dB	56.1 dB	58.1 dB	49.7 dB	52.7 dB	24.5 dB	100 ± 15 Ohm	100 ± 15 Ohm
10 MHz	5.8 db/100m	61.8 dB	59.8 dB	54 dB	56 dB	47.8 dB	50.8 dB	25 dB	100 ± 15 Ohm	100 ± 15 Ohm
16 MHz	7.4 db/100m	58.6 dB	56.6 dB	49.2 dB	51.2 dB	43.7 dB	46.7 dB	25 dB	100 ± 15 Ohm	100 ± 15 Ohm
20 MHz	8.3 db/100m	57.1 dB	55.1 dB	46.8 dB	46.8 dB	41.8 dB	44.8 dB	25 dB	100 ± 15 Ohm	100 ± 15 Ohm
25 MHz	9.3 db/100m	55.5 dB	53.5 dB	44.3 dB	46.3 dB	39.8 dB	42.8 dB	24.3 dB	100 ± 15 Ohm	100 ± 15 Ohm
31.25 MHz	11.4 db/100m	54 dB	52 dB	41.6 dB	43.6 dB	37.9 dB	40.9 dB	23.6 dB	100 ± 15 Ohm	100 ± 15 Ohm
62.5 MHz	15 db/100m	49.1 dB	47.1 dB	32.1 dB	34.1 dB	31.9 dB	34.9 dB	21.5 dB	100 ± 15 Ohm	100 ± 15 Ohm
100 MHz	19.3 db/100m	45.8 dB	43.8 dB	24.5 dB	26.5 dB	27.8 dB	30.8 dB	20.8 dB	100 ± 15 Ohm	100 ± 15 Ohm
155 MHz	24.5 db/100m	42.7 dB	40.7 dB	16.2 dB	18.2 dB	24 dB	27 dB	19.8 dB	100 ± 15 Ohm	100 ± 15 Ohm
200 MHz	28.3 db/100m	40.9 dB	38.9 dB	10.6 dB	12.6 dB	21.8 dB	24.8 dB	18.7 dB	100 ± 22 Ohm	100 ± 15 Ohm
250 MHz	32.1 db/100m	39.3 dB	37.3 dB	5.2 dB	7.2 dB	19.8 dB	22.8 dB	18 dB	100 ± 32 Ohm	100 ± 15 Ohm
300 MHz	38 db/100m	38.1 dB	36.1 dB	-0.5 dB	2.5 dB	18.3 dB	21.3 dB	17.5 dB	100 ± 32 Ohm	100 ± 15 Ohm
350 MHz	38.9 db/100m	37.1 dB	35.1 dB	-3.7 dB	-1.7 dB	16.9 dB	19.9 dB	17 dB	100 ± 32 Ohm	100 ± 15 Ohm
400 MHz	42 db/100m	36.3 dB	34.3 dB	-7.7 dB	-5.7 dB	15.8 dB	18.8 dB	16.6 dB	100 ± 32 Ohm	100 ± 15 Ohm
450 MHz	45 db/100m	35.5 dB	33.5 dB	-11.5 dB	-9.5 dB	14.7 dB	17.7 dB	16.2 dB	100 ± 32 Ohm	100 ± 15 Ohm
500 MHz	47.9 db/100m	34.8 dB	32.8 dB	-15 dB	-13 dB	13.8 dB	16.8 dB	15.9 dB	100 ± 32 Ohm	100 ± 15 Ohm
550 MHz	50.6 db/100m	34.2 dB	32.2 dB	-18.4 dB	-16.4 dB	13 dB	16 dB	15.6 dB	100 ± 32 Ohm	100 ± 15 Ohm
Tested to 550Mhz - Values above 250Mhz are for Engineering Purposes Only										

Related Products

RELATED PRODUCTS	
Plenum Number	254246
Indoor/Outdoor Non Aquaseal	4246IO
Outdoor Direct Burial 1	4246OSP
Jack	KJ458MT-C6C-XX
Modular Plug	32-6EZP
Modular Plug 2	32-6198UL

Part Numbers

Part Number	Jacket Color	Put Up Length	Part Number	Jacket Color	Put Up Length
4246EZGY1000	GRAY	1000			
4246EZBK1000	BLACK	1000			
4246EZBL1000	BLUE	1000			
4246EZRD1000	RED	1000			
4246EZWH1000	WHITE	1000			
4246EZOR1000	ORANGE	1000			
4246EZGN1000	GREEN	1000			
4246EZYE1000	YELLOW	1000			
4246EZVT1000	VIOLET	1000			
4246EZTN1000	TAN	1000			
4246EZPK1000	PINK	1000			