Technical Data Sheet RG6/U CCTV + Power Coaxial Cable



2833 West Chestnut Street Washington, PA 15301 Toll Free: (800) 245-4964 Fax: (724) 222-6420 www.westpenn-cdt.com

	www.westpenn-cdt.com
PART NUMBER:	AQC2806
DESCRIPTION:	RG6/U 18AWG Bare Copper, 95% Braid + 2 Conductor 16AWG – Water blocking tapes Sunlight Resistant PVC Jacket - Siamese Construction
NEC RATING:	СМ
APPROVALS:	(UL) or (ETL)us Listed
APPLICATION:	CCTV Indoor/Outdoor Baseband video

Construction Parameters: Coaxial Cable

Conductor	18 AWG Bare Copper RG6/U	Nom At	tenuation
Stranding	Solid		0/100ft
Insulation Material	Gas Injected Polyethylene (PE)	1	.29
Insulation Thickness	0.180" Nom.	10	.68
Shield	95 % Bare Copper Braid	50	1.80
Jacket Material	Sunlight Resistant PVC	150	3.0
Electrical & Environmental Properties: Coaxial Cable			3.54
L		400	4.71
Temperature Rating	-20deg C to 60deg C	1000	7.80
Operating Voltage	300 V RMS		
Max. Capacitance Between Conductors @ 1 KHz	16.2pf/ft Nom.		
Nom. Velocity of Propagation	82%		

Construction Parameters: Power Pair

Conductor	16 AWG Bare Copper		
Stranding	Stranded		
Insulation Material	PVC		
Insulation Thickness	0.008" Nom.		
Number of Conductors	2		
Shield	None		
Drain	None		
Jacket Material	PVC		
Electrical & Environmental Properties: Power Pair			
Temperature Rating	-20°C To +60°C		
Operating Voltage	300 V RMS		

Operating Voltage Max. Capacitance Between Conductors @ 1 KHz DC Resistance per Conductor @ 20deg C Insulation Colors

Construction Parameters: Overall Cable

Jacket Material Overall Cable Diameter Jacket Colors Flame Rating RoHS Compliant PVC .280"x.580" Black UL1685 Yes

30 pf/ft Nom.

Black ,Red

4.4 Ohms/1M' Nom.

Mechanical Properties: Max. Recommended Pull Tension

Max. Recommended Pull Tension Min. Bend Radius (Install)

Connectors:	
750hm BNC Crimp	CN-BM73-5
Compression BNC	CN-BNC6MCV

Specification Issue Date: 4/12

This document is the property of West Penn Wire. The information contained herein is considered Proprietary and not to be reproduced by any means Without written consent of West Penn Wire -- Lbs. 5.80

Standard Lengths are 1000ft. The Jacket is sequentially footmarked. The information presented here is, to the best of our knowledge, is true and accurate. However, since conditions of use are beyond our control, all recommendations or suggestions are presented without guarantee or responsibility on our part. We disclaim all liability in connection with the use of information contained herein or otherwise.