Technical Data Sheet Aquaseal® Communication Cables





2833 West Chestnut Street Washington, PA 15301 Toll Free: (800) 245-4964 Fax: (724) 222-6420 www.westpenn-wpw.com



PART NUMBER: AQC369

DESCRIPTION: 22/6 Solid Bare copper conductor, unshielded/shielded, with an Aquaseal tape and overall jacket.

NEC RATING: CM or CL3, NEC Article 800 and 725

APPROVALS: (UL) Listed, (ETL)us Listed

APPLICATION: Materials suitable for outdoor use, and indoor trays, allows a variety of uses for (Intercom, Security,

Sound, Audio, Background music)

Construction Parameters:

Conductor 22 AWG Bare Copper Stranding Solid Insulation Material PVC Insulation Thickness 0.010" Nom.

Number of Conductors

(2 Shielded)(4 Unshielded)

Shield 100% Aluminum Polyester Foil

Drain Solid Tinned Copper

Water-Blocking Tape Internal and Overall 2 ply water swellable tape

Jacket Material Sunlight/Moisture Resistance PVC

Jacket Thickness0.025" Nom.Overall Cable Diameter0.240" Nom.Approximate Cable Weight30 Lbs/1M' Nom.

Flame Rating UL 1685 Vertical Tray

Electrical & Environmental Properties:

Temperature Rating -20deg C to 60deg C Operating Voltage 300 V RMS

Max.Capacitance Between Conductors @ 1 KHz 54 pf/ft Nom.
Capacitance Between Conductors to Shield @ 1 KHz 97 pf/ft Nom.

DC Resistance per Conductor @ 20deg C 17.5 Ohms/1M' Nom.

Insulation Colors Black, Red, White, Green, Brown, Blue

TIA455-82B Water Infiltration Test Compliant

Yes
UL 444 & 13 Compliant

Yes

Mechanical Properties:

Max. Recommended Pull Tension69 lbs.Min. Bend Radius (Install)2.4"

Specification Issue Date: 7/06

This document is the property of West Penn Wire. The information contained herein is considered Proprietary and not to be reproduced by any means Without written consent of West Penn Wire Standard Lengths are 1000ft.
The Jacket is sequentially footmarked.
The information presented here is, to the best of our knowledge, is true and accurate. However, since conditions of use are beyond our control, all recommendations or suggestions are presented without guarantee or responsibility on our part. We disclaim all liability in connection with the use of information contained herein or otherwise.