## Technical Data Sheet Professional Audio Snake





2833 West Chestnut Street Washington, PA 15301 Toll Free: (800) 245-4964 Fax: (724) 222-6420 www.westpenn-wpw.com

PART NUMBER: D25431

**DESCRIPTION:** 22 AWG.- 3 PAIR Stranded tinned copper conductors, individually shielded with an overall jacket.

NEC RATING: CMP

APPROVALS: (UL) Listed

**APPLICATION:** Indoor Plenum Area for: Intercom, Security, Sound, Audio, Background Music, and Power Limited

Control Circuits.

## **Construction Parameters:**

Conductor 22 AWG Tinned Copper

Stranding7x30Insulation MaterialTeflonInsulation Thickness0.010" Nom.Number of Conductors6 (3 Pair)

Shield Each Pair 100% Aluminum Foil
Drain Stranded Tinned Copper

Jacket MaterialFlex PlenumJacket Thickness0.017" Nom.Overall Cable Diameter0.232" Nom.Approximate Cable Weight38 Lbs/1M' Nom.Flame RatingNFPA 262

## **Electrical & Environmental Properties:**

Temperature Rating -20°C To +60°C Operating Voltage 300 V RMS Max.Capacitance Between Conductors @ 1 KHz 25 pf/ft Nom.

Capacitance Between Conductors to Shield @ 1 KHz 45 pf/ft Nom.

DC Resistance per Conductor @ 20deg C 17 Ohms/1M' Nom.

Insulation Colors

Black/Red-Red, Black/White-White,

Black/Green-Green

Jacket ColorGrayRoHS CompliantYes

## **Mechanical Properties:**

Max. Recommended Pull Tension74 Lbs.Min. Bend Radius (Install)2.6"

Specification Issue Date: 7/06

This document is the property of West Penn Wire. The information contained herein is considered Proprietary and not to be reproduced by any means Without written consent of West Penn Wire Standard Lengths are 1000ft.
The Jacket is sequentially footmarked.
The information presented here is, to the best of our knowledge, is true and accurate. However, since conditions of use are beyond our control, all recommendations or suggestions are presented without guarantee or responsibility on our part. We disclaim all liability in connection with the use of information contained herein or otherwise.