Technical Data Sheet Professional Audio Snake - Plenum



2833 West Chestnut Street Washington, PA 15301 Toll Free: (800) 245-4964 Fax: (724) 222-6420

	www.westpenn-wpw.com
PART NUMBER:	D25439
DESCRIPTION:	22 AWG 4 PAIR Stranded tinned copper conductors, individually shielded with an overall jacket.
NEC RATING:	СМР
APPROVALS:	(UL) Listed
APPLICATION:	Indoor Plenum Area for: Intercom, Security, Sound, Audio, Background Music, and Power Limited Control Circuits.

Construction Parameters:

Conductor 22 AWG Tinned Copper Stranding 7x30 Insulation Material Teflon 0.010" Nom. Insulation Thickness Number of Conductors 8 (4 Pair) Shield Each Pair 100% Aluminum Foil Drain Stranded Tinned Copper Jacket Material Flex Plenum Jacket Thickness 0.017" Nom. 0.256" Nom. **Overall Cable Diameter** Approximate Cable Weight 47 Lbs/1M' Nom. Flame Rating

Electrical & Environmental Properties:

Temperature Rating Operating Voltage Max.Capacitance Between Conductors @ 1 KHz Capacitance Between Conductors to Shield @ 1 KHz DC Resistance per Conductor @ 20deg C Insulation Colors

Jacket Color **RoHS** Compliant

Mechanical Properties:

Max. Recommended Pull Tension Min. Bend Radius (Install)

Specification Issue Date: 7/06

This document is the property of West Penn Wire. The information contained herein is considered Proprietary and not to be reproduced by any means Without written consent of West Penn Wire

NFPA 262

-20°C To +60°C 300 V RMS 25 pf/ft Nom. 45 pf/ft Nom. 17 Ohms/1M' Nom. Black/Red-Red, Black/White-White, Black/Green-Green, Black/Blue-Blue Gray Yes

80 Lbs. 2.5"

Standard Lengths are 1000ft. The Jacket is sequentially footmarked. The information presented here is, to the best of our knowledge, is true and accurate. However, since conditions of use are beyond our control, all recommendations or suggestions are presented without guarantee or responsibility on our part. We disclaim all liability in connection with the use of information contained herein or otherwise.