Technical Data Sheet Communication Cables



2833 West Chestnut Street Washington, PA 15301 Toll Free: (800) 245-4964 Fax: (724) 222-6420 www.westpenn-wpw.com

PART NUMBER: D430

DESCRIPTION: 22 AWG.- 2 PAIR Stranded tinned copper conductors, individually shielded with an overall jacket.

NEC RATING: CM, NEC Article 800

APPROVALS: (UL) C(UL) Listed or c(ETL)us Listed

APPLICATION: Indoor for: Intercom, Security, Sound, Audio, Background Music, and Power Limited Control

Circuits.

Construction Parameters:

Conductor 22 AWG Tinned Copper

Stranding 7/30
Insulation Material Polyolefin
Insulation Thickness 0.006" Nom.
Number of Conductors 4 (2 Pair)

Shield Each Pair 100% Aluminum Foil
Drain Stranded Tinned Copper

Jacket MaterialPVCJacket Thickness0.025" Nom.Overall Cable Diameter0.235" Nom.Approximate Cable Weight26 Lbs/1M' Nom.Flame RatingUL 1685 Riser Flame Test

Electrical & Environmental Properties:

Temperature Rating -20°C To +60°C
Operating Voltage 300 V RMS
Max.Capacitance Between Conductors @ 1 KHz 34 pf/ft Nom.
Capacitance Between Conductors to Shield @ 1 KHz 67 pf/ft Nom.

DC Resistance per Conductor @ 20deg C 17 Ohms/1M' Nom.
Insulation Colors Black/Red-Red, Black/White-White

Insulation Colors Black/Re
Jacket Color Gray
RoHS Compliant Yes

Mechanical Properties:

Max. Recommended Pull Tension
Min. Bend Radius (Install)

Specification Issue Date: 7/14

This document is the property of West Penn Wire. The information contained herein is considered Proprietary and not to be reproduced by any means Without written consent of West Penn Wire 55 Lbs. 2.4"



Standard Lengths are 1000ft.
The Jacket is sequentially footmarked.
The information presented here is, to the best of our knowledge, is true and accurate. However, since conditions of use are beyond our control, all recommendations or suggestions are presented without guarantee or responsibility on our part. We disclaim all liability in connection with the use of information contained herein or otherwise.