Technical Data Sheet Communication Cables



2833 West Chestnut Street Washington, PA 15301 Toll Free: (800) 245-4964 Fax: (724) 222-6420 www.westpenn-wpw.com



PART NUMBER: D434

DESCRIPTION: 22 AWG.- 12 PAIR Stranded tinned copper conductors, individually shielded with an overall jacket.

NEC RATING: CM, NEC Article 800

APPROVALS: (UL) C(UL) Listed or c(ETL)us Listed

APPLICATION: Indoor for: Intercom, Security, Sound, Audio, Background Music, and Power Limited Control

Circuits.

Construction Parameters:

Conductor 22 AWG Tinned Copper

Stranding 7x30
Insulation Material Polyolefin
Insulation Thickness 0.006" Nom.
Number of Conductors 24 (12 Pair)

Shield Each Pair 100% Aluminum Foil
Drain Stranded Tinned Copper

Jacket Material PVC
Jacket Thickness 0.034" Nom.
Overall Cable Diameter 0.420" Nom.
Approximate Cable Weight 128 Lbs/1M' Nom.

Flame Rating UL 1685

Electrical & Environmental Properties:

Temperature Rating -20°C To +60°C
Operating Voltage 300 V RMS
Max.Capacitance Between Conductors @ 1 KHz 34 pf/ft Nom.
Capacitance Between Conductors to Shield @ 1 KHz 67 pf/ft Nom.

DC Resistance per Conductor @ 20deg C 17 Ohms/1M' Nom.

Insulation Colors

Black/Red, Black/White, Black/Green,
Black/Blue, Black/Yellow, Black/Brown,

Black/Orange, Red/White,

Red/Green, Red/Blue, Red/Yellow,

Red/Brown-Brown

Jacket ColorGrayRoHS CompliantY

Mechanical Properties:

Max. Recommended Pull Tension 236 Lbs.
Min. Bend Radius (Install) 4.1"

Specification Issue Date: 7/14

This document is the property of West Penn Wire. The information contained herein is considered Proprietary and not to be reproduced by any means Without written consent of West Penn Wire Standard Lengths are 1000ft.
The Jacket is sequentially footmarked.
The information presented here is, to the best of our knowledge, is true and accurate. However, since conditions of use are beyond our control, all recommendations or suggestions are presented without guarantee or responsibility on our part. We disclaim all liability in connection with the use of information contained herein or otherwise.