

ONE SHEET

Overview

The PT3500 teleprompter system is designed for professionals needing to work quickly and efficiently in the field or studio.

Featuring solid, aluminum and steel construction, The PT3500 is a durable yet lightweight compact 15" teleprompter kit. The foundation is a 15mm Rod base system, which allows for simple height adjustments and a folding glass frame that makes it easy for you to set up and travel.

PT3500 | 15" Rod Based Location/Studio Teleprompter | UPC Code: 847983011490

Special Features

- New Adjustable Glass Frame
- Based on 15mm Rod System for Ease of Use
- Lightweight & Compact Design for Easy Travel
- Ships in Reusable Foam for Easy Transport
- High Quality Monitor w/ Metal Construction
- High Quality American Made 70/30 Teleprompter Glass
- Includes MAC and PC Software

Recommened For

- Studio
- Location




www.facebook.com/ikanseeit

www.twitter.com/ikancorp

www.vimeo.com/ikancorp

www.youtube.com/ikancorp







Features you need, Prices you want.

Adjustable Glass Frame

The adjustable glass frame on the PT3500 allows for fast and easy set up. The frame can also be folded to make the teleprompter compact and easy to transport.



Dual Purpose Unique Base Plate

The dual purpose base plate supports various cameras, DSLRs and small to mid-sized cameras. A unique feature of the base plate is the DSLR shelf which allows you to put a DSLR camera at the very edge of the base plate to get closer if needed.

200mm Height Adjustment Rods

The PT3500 includes two height adjustment rods, 130mm and 200mm, making the teleprompter more versatile for various sized cameras.

High Quality 70/30 Teleprompter Glass

The high quality 70/30 teleprompter glass provides the perfect balance of reflection and passthrough without distorting the image. This high quality allows your camera to have a great picture, while providing the reflection you need to read the text.



Accessories

IDX-1204 12 Channel DMX Console



ikan

MK350 MK350 Spectometer



Specifications	
Aspect Ratio	4:3
Brightness	350 cd/m2
Build Material	Aluminum / Steel
Contrast Ratio	500:1
Diagonal	15"
Input Signal	Composite BNC, VGA, HDMI
Input Voltage	DC 12v / 4A
Operating Volts	DC 12v / 4A
Power Consumption	10 w
Reading Range	20'
Resolution	1024 x 768
Supported Video Signals	0-65 C
Viewing Angle	160° (H) / 140° (V)
Weight	15 lbs
Shipping Weight	21 lbs
Shipping Dimensions	29.5" x 19" x 10.5"

Ships in Reusable Foam

The PT3500 is shipped in reusable custom cut foam which will help keep the kit safe and organized when you set it up or break it down. The custom cut foam can also be repurposed to perfectly fit in the SKB (Series 2918-10 Waterproof Hard Case-Featured in image).



Includes Software for Mac & PC

The PrompterPro3 Teleprompting software for Mac and PC are included in this kit. This software offers a full text editor, vertical and horizontal screen flip, real-time text updates, and live prompter mode for optional control. The software is compatible with Mac OSX 10.7 (and up on 64-bit processor) and Windows XP, Vista, 7, & 8.



sales@ikancorp.com

Houston, Texas

www.ikancorp.com

1.713.272.8822