

HDMI 2.0 to DisplayPort 1.2 Converter USER MANUAL

HDMI-DP-UHD



Package Contents

- 1 x HDMI-DP-UHD
- 1 x 12V Locking PS
- 1 x Mounting Plate
- 1 x User Manual

Features

- HDMI 2.0/1.4 compliant
- Supports UHD@60Hz 4:4:4
- DisplayPort 1.2a compliant
- Supports SST
- 2 DisplayPort outputs, supports RBR/HBR/HBR2
- Stereo audio output
- HDCP 2.2/1.4 compliant

Specifications

Functions	HDMI-DP-UHD
Input Connector	1 x HDMI 2.0
Output Connector	2 x DP 1.2a
Audio	Stereo, 32K ~ 192 KHz
Maximum Resolution	4Kx2K@60Hz 4:4:4
Power	DC 12V 1.2A
Weight	360 g
Dimension	108x114x25 mm
Environment	Operating Temp 0 ~ 45C Operating Humidity 20 ~ 90% Storage Temp - 20 ~ 60C

FRONT VIEW




1. Micro USB – reserved for service
2. DisplayPort Input connector
3. LED status indicators
 - a. Link
 - i. Off on initial power on
 - ii. blinking when waiting for Sink to be

- iii. Steady blue when the sink EDID ready
 - b. Power – Red when there is power
4. Power Jack – 12V DC

REAR VIEW



1. Dual DisplayPort outputs



© 2017 APANTAC LLC, All rights reserved
7470 SW BRIDGEPORT ROAD
PORTLAND, OR 97224, USA
PHONE +1 503 968 3000, FAX +1 503 389 7921

The content of this document are provided in connection with Apantac LLC ("Apantac") products. Apantac makes no representation or warranties with respect to the accuracy or completeness of the contents of this publication and reserves the right to make changes to specification and product descriptions at any time without notice