


Camera Fixing



It is important that the camera lens is in the centre of the aperture at the rear of the hood. This is achieved by raising and lowering the camera mounting plate and hood.



1/4" BSW

Camera Screw

Fix the camera in place using the camera screw provided.



SSP10



By replacing the iPad holder with the 10" display it is possible to convert your iPad Portable into an SSP10.

Alternative Configuration

The iPad Portable can be reconfigured to straight read mode. To achieve this remove the hood unit by loosening the two thumb screws of the iPad holder and move the monitor to the vertical position.



Correct iPad orientation for straight read

iPad Portable Guide



Components

A	Hood and Glass
B	iPad Holder
C	Camera Mounting Plate
D	Hood Adjustment Clamps




Assembly

1. Fix the hot shoe from your tripod to the underside of the mounting plate. Slide the hot shoe to the approximate position and tighten the screws.



2. Mount the unit on the tripod.

3. Loosen the thumb screws at the side of the iPad holder. Unfold the holder and slide into position.




4. Position your iPad between the clamps of the iPad holder.



5. Hold in place by positioning the clamps over the corners of the iPad.

6. Tighten the thumb screws (A) on the underside of the mounting to secure the iPad.



B

7. Loosen the thumb screws (B) on the hood assembly.



8. Lift the hood into position and retighten to secure in place.

Mounting the Camera

1. For larger cameras the mounting plate may need extending. Loosen the four thumb screws on the camera plate and remove the rear two, the plate will now slide out. Replace the two rear screws and tighten them to secure the plate.



Pillar Kit

2. For smaller cameras the camera plate will need to be raised. Remove the four thumb screws and lift off the plate.



3. Install four camera plate pillars of the appropriate height.

4. Re-fix the camera plate using the four screws provided.



Pillar combinations

To achieve the maximum height, combine two pillars.