

INSTALLATION INSTRUCTIONS



VESA Interface Bracket

DISCLAIMER

Milestone AV Technologies, and its affiliated corporations and subsidiaries (collectively, "Milestone"), intend to make this manual accurate and complete. However, Milestone makes no claim that the information contained herein covers all details, conditions or variations, nor does it provide for every possible contingency in connection with the installation or use of this product. The information contained in this document is subject to change without notice or obligation of any kind. Milestone makes no representation of warranty, expressed or implied, regarding the information contained herein. Milestone assumes no responsibility for accuracy, completeness or sufficiency of the information contained in this document.

®Chief is a registered trademark of Milestone AV Technologies. All rights reserved.



IMPORTANT SAFETY INSTRUCTIONS!



WARNING: A WARNING alerts you to the possibility of serious injury or death if you do not follow the instructions.



CAUTION: A CAUTION alerts you to the possibility of damage or destruction of equipment if you do not follow the corresponding instructions.



WARNING: Failure to read, thoroughly understand, and follow all instructions can result in serious personal injury, damage to equipment, or voiding of factory warranty! It is the installer's responsibility to make sure all components are properly assembled and installed using the instructions provided.



WARNING: Failure to provide adequate structural strength for this component can result in serious personal injury or damage to equipment! It is the installer's responsibility to make sure the structure to which this component is attached can support five times the combined weight of all equipment. Reinforce the structure as required before installing the component.



WARNING: Exceeding the weight capacity can result in serious personal injury or damage to equipment! It is the installer's responsibility to make sure the combined weight of all components attached to the MSBV does not exceed 125 lbs (56.7 kg).



WARNING: Use this mounting system only for its intended use as described in these instructions. Do not use attachments not recommended by the manufacturer.



WARNING: Never operate this mounting system if it is damaged. Return the mounting system to a service center for examination and repair.



WARNING: Do not use this product outdoors.

NOTE: The MSBV interface bracket is compatible with the following VESA patterns:


- 100 x 100mm
- 200 x 100mm
- 200 x 200mm
- 300 x 100mm
- 300 x 200mm
- 400 x 200mm

IMPORTANT ! : The MSBV interface brackets are designed to be mounted to a:

- Listed Chief MCD6000 dual ceiling mount;
- Listed Chief MCS6000 single ceiling mount.

--SAVE THESE INSTRUCTIONS--

DIMENSIONS




LEGEND














	Tighten Fastener		Phillips Screwdriver
	Apretar elemento de fijación		Destornillador Phillips
	Befestigungsteil festziehen		Kreuzschlitzschraubendreher
	Apertar fixador		Chave de fendas Phillips
	Serrare il fissaggio		Cacciavite a stella
	Bevestiging vastdraaien		Kruiskopschroevendraaier
	Serrez les fixations		Tournevis à pointe cruciforme
Сожмите Застежку	Отвертка		
	Loosen Fastener		
	Aflojar elemento de fijación		
	Befestigungsteil lösen		
	Desapertar fixador		
	Allentare il fissaggio		
	Bevestiging losdraaien		
	Desserrez les fixations		
Ослабьте Застежку			

TOOLS REQUIRED FOR INSTALLATION



PARTS



<p>Bag A</p> <div style="display: flex; justify-content: space-around;"> <div style="text-align: center;">  A (8) M4 x 12mm </div> <div style="text-align: center;">  B (8) M4 x 25mm </div> </div>	
<p>Bag B</p> <div style="display: flex; justify-content: space-around;"> <div style="text-align: center;">  C (8) M5 x 12mm </div> <div style="text-align: center;">  D (8) M5 x 25mm </div> </div> <div style="display: flex; justify-content: space-around; margin-top: 20px;"> <div style="text-align: center;">  E (8) M5 x 30mm </div> <div style="text-align: center;">  F (8) M5 x 45mm </div> </div>	
<p>Bag C</p> <div style="display: flex; justify-content: space-around;"> <div style="text-align: center;">  G (8) M6 x 12mm </div> <div style="text-align: center;">  H (8) M6 x 25mm </div> </div> <div style="display: flex; justify-content: space-around; margin-top: 20px;"> <div style="text-align: center;">  J (8) M6 x 30mm </div> <div style="text-align: center;">  K (8) M6 x 45mm </div> </div>	
<p>Bag D</p> <div style="display: flex; justify-content: space-around;"> <div style="text-align: center;">  L (8) .750x.344x.500 </div> <div style="text-align: center;">  M (4) M4 </div> <div style="text-align: center;">  N (4) 7mm </div> </div>	

Guidelines for Using Spacers (if required)

If the display has a recessed mounting surface, protrusions or a power box, a spacer must be placed between the display and MSBV bracket (A) and longer mounting hardware must be used. (See Figure 1)




Figure 1

IMPORTANT ! : Proceed to the correct procedure for installation of MSBV based upon the display’s mounting pattern.

INSTALLATION



WARNING: IMPROPER INSTALLATION CAN LEAD TO DISPLAY FALLING CAUSING SERIOUS PERSONAL INJURY OR DAMAGE TO EQUIPMENT! Using screws of improper size may damage your display. Properly sized screws will easily and completely thread into display mounting holes. If spacers are required, be sure to use longer screws of the same diameter.

100 x 100mm Pattern

1. Select **four** properly sized M4 screws from Bag A.
2. Attach the MSBV bracket (A) using the hole pattern on back of display and holes noted at "X". (See Figure 2)
3. To prevent equipment damage, do not over-tighten the screws into the display.




Figure 2

200 x 100mm Pattern

1. Select **six** properly sized M4 screws from Bag A.
2. Attach the MSBV bracket (A) using the hole pattern on back of display and holes noted at "X". (See Figure 3)
3. To prevent equipment damage, do not over-tighten the screws into the display.




Figure 3

300 x 100mm Pattern

1. Select **eight** properly sized M4 screws from Bag A.
2. Attach the MSBV bracket (A) using the hole pattern on back of display and holes noted at "X". (See Figure)
3. To prevent equipment damage, do not over-tighten the screws into the display.




Figure 4

400 x 200mm Pattern

1. Select **six** M5 or M6 screws from Bag B or Bag C.
2. Attach the MSBV bracket (A) using the hole pattern on back of display and holes noted at "X". (See Figure 6)
3. To prevent equipment damage, do not over-tighten the screws into the display.




Figure 6

300 x 200mm Pattern

1. Select **eight** M5 or M6 screws from Bag B or Bag C.
2. Attach the MSBV bracket (A) using the hole pattern on back of display and holes noted at "X". (See Figure 5)
3. To prevent equipment damage, do not over-tighten the screws into the display.




Figure 5

200 x 200mm Pattern

Select the appropriate method for attaching mounting buttons **directly to display**, dependent on size of mounting screw required for your display.

1. **If mounting screw is M4**, attach four mounting buttons (Q) using four shoulder washers (N), four M4 washers (M) and four M4 screws from Bag A. (See Figure 7)
2. **If mounting screw is M5 or M6**, attach four mounting buttons (Q) using four M5 or M6 screws from Bag B or Bag C. (See Figure 7)




Figure 7

3. If 200 x 200mm hole pattern is shifted high on the screen, attach the MSBV bracket (A) vertically with four M5 or M6 screws (Bag B or Bag C). (See Figure 8)




Figure 8

INSTALLING DISPLAY TO MOUNT

1. Install display to UL Listed Chief mount following instructions included with the mount.



Our Mounts. **Your Vision.**

Chief, a products division of
Milestone AV Technologies

8800-002592 Rev02

©2014 Milestone AV Technologies

www.chiefmfg.com

05/14

USA/International	A 6436 City West Parkway, Eden Prairie, MN 55344
	P 800.582.6480 / 952.225.6000
	F 877.894.6918 / 952.894.6918
Europe	A Franklinstraat 14, 6003 DK Weert, Netherlands
	P +31 (0) 495 580 852
	F +31 (0) 495 580 845
Asia Pacific	A Office No. 918 on 9/F, Shatin Galleria 18-24 Shan Mei Street Fotan, Shatin, Hong Kong
	P 852 2145 4099
	F 852 2145 4477

